

Overview

Models

HP MSR20-10 Router	JD431A
HP MSR20-11 Router	JF239A
HP MSR20-12 Router	JF241A
HP MSR20-12-W Router	JF807A
HP MSR20-12-T Router	JF806A
HP MSR20-12-T-W Router (NA)	JG209A
HP MSR20-13 Router	JF240A
HP MSR20-13-W Router	JF808A
HP MSR20-13-W Router (NA)	JG210A
HP MSR20-15-A Router	JF237A
HP MSR20-15-A-W Router	JF809A
HP MSR20-15-I Router	JF236A
HP MSR20-15-I-W Router	JF238A
HP MSR20-15 Router	JF817A

Key features

- Routing, switching, security, wireless, and voice
- Compact design for both desktop and rackmounting
- Fixed-port and modular WAN/LAN interface options
- Embedded encryption, firewall, security features
- Single-pane-of-glass management

Product overview

The HP MSR20-1x Series is a component of the HP FlexBranch solution, which is part of the HP FlexNetwork architecture. MSR20-1X routers are full-featured, economical routers designed for converged wired and wireless WAN and LAN environments at small remote branch offices and small to medium-sized businesses. HP MSR20-1x series routers deliver high-performance integrated routing, switching, security, wireless, and voice services while reducing complexity, simplifying management, and increasing control. These routers enable an agile and flexible network infrastructure that can quickly adapt to changing business requirements while delivering integrated services on a single, easy-to-manage platform.

Features and benefits

Quality of Service (QoS)

- **Traffic policing**—supports Committed Access Rate (CAR) and line rate
- **Congestion management**—supports FIFO, PQ, CQ, WFQ, CBQ, and RTPQ
- **Congestion avoidance**—Weighted Random Early Detection (WRED)/Random Early Detection (RED)
- **Other QoS technologies**—support traffic shaping, FR QoS, MPLS QoS, and MP QoS/LFI

Overview

Management

- **Industry-standard CLI with a hierarchical structure**—reduces training time and expenses, and increases productivity in multivendor installations
- **Management security**—multiple privilege levels with password protection restrict access to critical configuration commands—ACLs provide telnet and SNMP access—local and remote syslog capabilities allow logging of all access
- **SNMPv1, v2, and v3**—provide complete support of SNMP—provide full support of industry-standard Management Information Base (MIB) plus private extensions—SNMPv3 supports increased security using encryption
- **Remote monitoring (RMON)**—uses standard SNMP to monitor essential network functions—supports events, alarm, history, and statistics group plus a private alarm extension group
- **FTP, TFTP, and SFTP support**—FTP allows bidirectional transfers over a TCP/IP network and is used for configuration updates—Trivial FTP is a simpler method using User Datagram Protocol (UDP)
- **Debug and sampler utility**—supports ping and traceroute for both IPv4 and IPv6
- **Network Time Protocol (NTP)**—synchronizes timekeeping among distributed time servers and clients—keeps timekeeping consistent among all clock-dependent devices within the network so that the devices can provide diverse applications based on the consistent time
- **Info center**—provides a central information center for system and network information—aggregates all logs, traps, and debugging information generated by the system and maintains them in order of severity—outputs the network information to multiple channels based on user-defined rules
- **Management interface control**—provides management access through modem port and terminal interface—provides access through terminal interface, telnet, or SSH
- **Network Quality Analyzer (NQA)**—analyzes network performance and service quality by sending test packets, and provides network performance and service quality parameters such as jitter, TCP, or FTP connection delays—allows network manager to determine overall network performance and diagnose and locate network congestion points or failures

Connectivity

- **Packet storm protection**—protects against broadcast, multicast, or unicast storms with user-defined thresholds
- **Loopback**—supports internal loopback testing for maintenance purposes and an increase in availability—loopback detection protects against incorrect cabling or network configurations and can be enabled on a per-port or per-VLAN basis for added flexibility
- **3G access support**—provides 3G wireless access for primary or backup connectivity via a 3G SIC module certified on various cellular networks—optional carrier 3G USB modems available
- **Flexible port selection**—provides a combination of fiber and copper interface modules, 100/1000BASE-X auto-speed selection, and 10/100/1000BASE-T auto-speed detection plus auto duplex and MDI/MDI-X
- **Multiple WAN interfaces**—provide a traditional link with E1, T1, ADSL, ADSL2, ADSL2+, G.SHDSL, ATM, Serial, and ISDN/AM backup—provide high-density Ethernet access with WAN Fast Ethernet/Gigabit Ethernet and LAN 4- and 9-port Fast Ethernet—provide mobility access with 802.11b/g/n Wi-Fi and 3G
- **High-density port connectivity**—includes one interface module slot and up to 10 Fast Ethernet ports

Performance

- **Powerful encryption capacity**—includes embedded hardware encryption accelerator to improve encryption performance
- **Flexible chassis selection**—offers a choice of 12 routers, meeting different requirements on enterprise branches
- **Excellent forwarding performance**—provides forwarding performance up to 160 Kpps—meets current and future bandwidth-intensive application demands of enterprise businesses

Resiliency and high availability



Overview

- **Backup Center**—acts as a part of the management and backup function to provide backup for device interfaces—delivers reliability by switching traffic over to a backup interface when the primary one fails
- **Virtual Router Redundancy Protocol (VRRP)**—allows groups of two routers to dynamically back each other up to create highly available routed environments—supports VRRP load balancing

Layer 2 switching

- **Spanning Tree Protocol (STP)**
fully supports standard IEEE 802.1D STP, IEEE 802.1w Rapid Spanning Tree Protocol (RSTP) for faster convergence, and IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
- **Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) protocol snooping**—effectively control and manage the flooding of multicast packets in a Layer 2 network
- **Port mirroring**—duplicates port traffic (ingress and egress) to a local or remote monitoring port
- **VLANs**—support IEEE 802.1Q-based VLANs
- **sFlow**—allows traffic sampling

Layer 3 services

- **Address Resolution Protocol (ARP)**—determines the MAC address of another IP host in the same subnet—supports static ARPs—gratuitous ARP allows detection of duplicate IP addresses—proxy ARP allows normal ARP operation between subnets or when subnets are separated by a Layer 2 network
- **User Datagram Protocol (UDP) helper**—redirects UDP broadcasts to specific IP subnets to prevent server spoofing
- **Dynamic Host Configuration Protocol (DHCP)**—simplifies the management of large IP networks and supports client and server—DHCP Relay enables DHCP operation across subnets

Layer 3 routing

- **Static IPv4 routing**
provides simple, manually configured IPv4 routing
- **Routing Information Protocol (RIP)**
uses a distance vector algorithm with UDP packets for route determination—supports RIPv1 and RIPv2 routing—includes loop protection
- **Open Shortest Path First (OSPF)**
Interior Gateway Protocol (IGP) uses link-state protocol for faster convergence—supports ECMP, NSSA, and MD5 authentication for increased security and graceful restart for faster failure recovery
- **Border Gateway Protocol 4 (BGP-4)**
Exterior Gateway Protocol (EGP) with path vector protocol uses TCP for enhanced reliability for the route discovery process, reduces bandwidth consumption by advertising only incremental updates, and supports extensive policies for increased flexibility, as well as scales to very large networks
- **Intermediate system to intermediate system (IS-IS)**
Interior Gateway Protocol (IGP) uses path vector protocol, which is defined by the ISO organization for IS-IS routing and extended by IETF RFC 1195 to operate in both TCP/IP and the OSI reference model (Integrated IS-IS)
- **Static IPv6 routing**
provides simple, manually configured IPv6 routing
- **Dual IP stack**
maintains separate stacks for IPv4 and IPv6 to ease the transition from an IPv4-only network to an IPv6-only network design

Overview

- **Routing Information Protocol next generation (RIPng)**
extends RIPv2 to support IPv6 addressing
- **OSPFv3**
provides OSPF support for IPv6
- **BGP+**
extends BGP-4 to support Multiprotocol BGP (MBGP), including support for IPv6 addressing
- **IS-IS for IPv6**
extends IS-IS to support IPv6 addressing
- **IPv6 tunneling**
is an important element for the transition from IPv4 to IPv6—allows IPv6 packets to traverse IPv4-only networks by encapsulating the IPv6 packet into a standard IPv4 packet—supports manually configured, 6to4, and Intra-Site Automatic Tunnel Addressing Protocol (ISATAP) tunnels
- **Multiprotocol Label Switching (MPLS)**
uses BGP to advertise routes across Label Switched Paths (LSPs), but uses simple labels to forward packets from any Layer 2 or Layer 3 protocol, thus reducing complexity and increasing performance—supports graceful restart for reduced failure impact—supports LSP tunneling and multilevel stacks
- **Multiprotocol Label Switching (MPLS) Layer 3 VPN**
allows Layer 3 VPNs across a provider network—uses Multiprotocol BGP (MP-BGP) to establish private routes for increased security—supports RFC 2547bis multiple autonomous system VPNs for added flexibility—supports IPv6 MPLS VPN
- **Multiprotocol Label Switching (MPLS) Layer 2 VPN**
establishes simple Layer 2 point-to-point VPNs across a provider network using only MPLS Label Distribution Protocol (LDP)—requires no routing and therefore decreases complexity, increases performance, and allows VPNs of non-routable protocols—uses no routing information for increased security—supports Circuit Cross Connect (CCC), Static Virtual Circuits (SVCs), Martini draft, and Kompella-draft technologies
- **Policy routing**
allows custom filters for increased performance and security—supports ACLs, IP prefix, AS paths, community lists, and aggregate policies

Security

- **Access control list (ACL)**—supports powerful ACLs for both IPv4 and IPv6—ACLs are used for filtering traffic to prevent unauthorized users from accessing the network, or for controlling network traffic to save resources—rules can either deny or permit traffic to be forwarded—rules can be based on a Layer 2 header or a Layer 3 protocol header—rules can be set to operate on specific dates or times
- **TACACS+**—is an authentication tool using TCP with encryption of the full authentication request that provides additional security
- **Network login**—standard IEEE 802.1x allows authentication of multiple users per port
- **RADIUS**—eases security access administration by using a password authentication server
- **Network address translation (NAT)**—supports one-to-one NAT, many-to-many NAT, and NAT control, enabling NAT-PT to support multiple connections—supports blacklist in NAT/NAT-PT, a limit on the number of connections, session logs, and multi-instances
- **Secure Shell (SSHv2)**—uses external servers to securely login into a remote device or securely login into MSR from a remote location—with authentication and encryption, it protects against IP spoofing and plain text password interception—increases the security of SFTP transfers
- **Unicast Reverse Path Forwarding (URPF)**—allows normal packets to be forwarded correctly, but discards the attaching packet due to lack of reverse path route or incorrect inbound interface—prevents source spoofing and distributed attacks
- **IPSec VPN**—supports DES, 3DES, and AES 128/192/256 encryption, and MD5 and SHA-1 authentication
- **DVPN (Dynamic Virtual Private Network)**—collects, maintains, and distributes dynamic public addresses through the VPN Address

Overview

Management (VAM) protocol, making VPN establishment available between enterprise branches that use dynamic addresses to access the public network—compared to traditional VPN technologies, DVPN technology is more flexible and has richer features, such as NAT traversal of DVPN packets, AAA identity authentication, IPSec protection of data packets, and multiple VPN domains

Convergence

- **Internet Group Management Protocol (IGMP)**—is used by IP hosts to establish and maintain multicast groups—supports IGMPv1, v2, and v3—utilizes Any-Source Multicast (ASM) or Source-Specific Multicast (SSM) to manage IPv4 multicast networks
- **Protocol Independent Multicast (PIM)**—is used for IPv4 and IPv6 multicast applications—supports PIM Dense Mode (PIM-DM), Sparse Mode (PIM-SM), and Source-Specific Mode (PIM-SSM)
- **Multicast Source Discovery Protocol (MSDP)**—is used for inter-domain multicast applications, allowing multiple PIM-SM domains to interoperate
- **Multicast Border Gateway Protocol (MBGP)**—allows multicast traffic to be forwarded across BGP networks and kept separate from unicast traffic

Integration

- **Embedded NetStream**—local and global server load-balancing module improves traffic distribution using powerful scheduling algorithms, including Layer 4 to 7 services—monitors the health status of servers and firewalls
- **Embedded VPN firewall**—provides enhanced stateful packet inspection and filtering—delivers advanced VPN services with Triple DES (3DES) and Advanced Encryption Standard (AES) encryption at high performance and low latency, Web content filtering, and application prioritization and enhancement

Additional information

- **OPEX savings**—are delivered through the use of a common operating system that simplifies and streamlines deployment, management, and training, thereby cutting costs as well as reducing the chance for human errors associated with having to manage multiple operating systems across different platforms and network layers
- **High reliability**—provides a state-of-the-art unified code base
- **Faster time to market**—engineering efficiencies allow new and custom features to be brought rapidly to the market with better initial and ongoing stability
- **Green initiative support**—provides support for RoHS and WEEE regulations

Product architecture

- **Ideal multiservice platform**—provides WAN router, Ethernet switch, wireless LAN, 3G WAN, firewall, VPN, and SIP/voice gateway all in one box
- **Flexible voice interfaces**—analog and digital voice interface options for easy integration within a wide range of deployments (E1 and T1 supported on MSR20-10/11/12/15 models—additional voice processor module required)
- **USB interface**—uses USB memory disk to download and upload configuration files—supports external USB 3G modem for 3G WAN uplink
- **Flexible modular design**—includes multiple types of modules that meet different requirements, such as Smart Interface Cards (SICs), which are small and cost-effective modules—Multi-functional Interface Modules (MIMs), which are more high-density and affordable modules—Flexible Interface Cards (FICs), which provide high reliability and are hot-swappable—and double-width modules, which provide high density

Warranty and support



Overview

- **1-year warranty**—with advance replacement and delivery (available in most countries)
- **Electronic and telephone support**—limited electronic and telephone support is available from HP—to reach our support centers, refer to www.hp.com/networking/contact-support for details on the duration of support provided with your product purchase, refer to www.hp.com/networking/warrantysummary
- **Software releases**—to find software for your product, refer to www.hp.com/networking/support for details on the software releases available with your product purchase, refer to www.hp.com/networking/warrantysummary

Configuration

Build To Order²

BTO is a standalone unit with no integration. BTO products ship standalone are not part of a CTO or Rack-Shippable solution.

HP MSR20-10 Router

- 1 - SIC module slot
- 1 - 256MB DDR SDRAM included
- 0 - ESM Slot
- 0 - VCPM slots
- 1 - VPM slot

JD431A
[See Configuration Note¹, 2, 9](#)

Russian Reduced Encryption

JD431A#A59

HP MSR20-11 Router

- 1 - SIC module slot
- 1 - 256MB DDR SDRAM included
- 0 - ESM Slot
- 0 - VCPM slots
- 1 - VPM slot

JF239A
[See Configuration Note¹, 2, 9](#)

Russian Reduced Encryption

JF239A#A59

HP MSR20-12 Router

- 1 - SIC module slot
- 1 - 256MB DDR SDRAM included
- 0 - ESM Slot
- 0 - VCPM slots
- 1 - VPM slot

JF241A
[See Configuration Note¹, 2, 9](#)

Russian Reduced Encryption

JF241A#A59

HP MSR20-12-T Router

- 1 - SIC module slot
- 1 - 256MB DDR SDRAM included
- 0 - ESM Slot
- 0 - VCPM slots
- 1 - VPM slot

JF806A
[See Configuration Note¹, 2, 9](#)

Russian Reduced Encryption

JF806A#A59

HP MSR20-12-W Router

JF807A



Configuration

- 1 - SIC module slot
- 1 - 256MB DDR SDRAM included
- 0 - ESM Slot
- 0 - VCPM slots
- 1 - VPM slot

See Configuration
Note^{1, 2, 9}

Russian Reduced Encryption

JF807A#A59

HP MSR20-13 Router

- 1 - SIC module slot
- 1 - 256MB DDR SDRAM included
- 0 - ESM Slot
- 0 - VCPM slots
- 0 - VPM slot

JF240A

See Configuration
Note^{1, 2, 9}

Russian Reduced Encryption

JF240A#A59

HP MSR20-13-W Router

- 1 - SIC module slot
- 1 - 256MB DDR SDRAM included
- 0 - ESM Slot
- 0 - VCPM slots
- 0 - VPM slot

JF808A

See Configuration
Note^{1, 2, 9}

Russian Reduced Encryption

JF808A#A59

HP A-MSR20-13-W Router (NA)

- 1 - SIC module slot
- 1 - 256MB DDR SDRAM included
- 0 - ESM Slot
- 0 - VCPM slots
- 0 - VPM slot

JG210A

See Configuration
Note^{1, 9}

HP MSR20-15-A-W Router

- 1 - SIC module slot
- 1 - 256MB DDR SDRAM included
- 0 - ESM Slot
- 0 - VCPM slots
- 1 - VPM slot

JG209A

See Configuration
Note^{1, 9}

HP MSR20-15-I Router

- 1 - SIC module slot
- 1 - RJ-45 ADSL2+ port

JF236A

See Configuration
Note^{1, 2, 9}



Configuration

- 1 - ISDN port
- 1 - 256MB DDR SDRAM included
- 0 - ESM Slot
- 0 - VCPM slots
- 1 - VPM slot

Russian Reduced Encryption

JF236A#A59

HP MSR20-15-A-W Router

- 1 - SIC module slot
- 1 - 256MB DDR SDRAM included
- 0 - ESM Slot
- 0 - VCPM slots
- 1 - VPM slot

JF809A

[See Configuration Note](#) 1, 2, 9

Russian Reduced Encryption

JF809A#A59

HP MSR20-15-A Router

- 1 - SIC module slot
- 1 - 256MB DDR SDRAM included
- 0 - ESM Slot
- 0 - VCPM slots
- 1 - VPM slot

JF237A

[See Configuration Note](#) 1, 2, 9

Russian Reduced Encryption

JF237A#A59

HP MSR20-15-I-W Router

- 1 - SIC module slot
- 1 - 256MB DDR SDRAM included
- 0 - ESM Slot
- 0 - VCPM slots
- 1 - VPM slot

JF238A

[See Configuration Note](#) 1, 2, 9

Russian Reduced Encryption

JF238A#A59

HP MSR20-15 Router

- 1 - SIC module slot
- 1 - 256MB DDR SDRAM included
- 0 - ESM Slot
- 0 - VCPM slots
- 1 - VPM slot

JF817A

[See Configuration Note](#) 1, 2, 9

Russian Reduced Encryption

JF817A#A59



Configuration

Configuration Rules²

- Note 1 AC Power Supply included
- Note 2 If this product is ordered for delivery to Russia, it must be ordered with the A59 option (also allowed for other countries desiring Low Encryption), then #A59 is the required option in addition to Localization options.
- Note 9 Localization required. (See Localization Menu)

Internal Power Supplies

Internal Power Supplies included

Modules

SIC Modules

HP MSR 4-port 10/100 SIC Module	JD573B
<ul style="list-style-type: none"> None 	
HP MSR 9-port 10/100 DSIC Module	JD574B
	See Configuration Note ²
HP MSR 1-port 10/100 SIC Module	JD545B
<ul style="list-style-type: none"> None 	
HP 1-port 100Mbt SFP SIC Router Module	JF280A
<ul style="list-style-type: none"> min=0 \ max=1 SFP Transceivers 	See Configuration Note ⁴
HP MSR 1-port 10/100/1000 SIC Module	JD572A
<ul style="list-style-type: none"> min=0 \ max=1 SFP Transceivers 	See Configuration Note ⁵
HP MSR 2-port FX0 SIC Module	JD558A
<ul style="list-style-type: none"> None 	
HP MSR 1-port FX0 SIC Module	JD559A
<ul style="list-style-type: none"> None 	

Configuration

HP MSR 2-port FXS SIC Module	JD560A
<ul style="list-style-type: none">• None	
HP MSR 1-port FXS SIC Module	JD561A
<ul style="list-style-type: none">• None	
HP MSR 1-port E1-Voice SIC Module	JD575A
<ul style="list-style-type: none">• min=0 \ max=1 E1 Cable	See Configuration Note-1, 6, 11
HP MSR 1-port T1-Voice SIC Module	JD576A
<ul style="list-style-type: none">• min=0 \ max=1 E1 Cable	See Configuration Note-1, 7
HP 2p ISDN-S/T Voice Interface SIC Mod	JF821A
<ul style="list-style-type: none">• None	
HP MSR 2FXS + 1FXO Voice Intfc SIC Mod	JD632A
<ul style="list-style-type: none">• None	
HP MSR 1-port Fractional E1 SIC Module	JD634B
<ul style="list-style-type: none">• min=0 \ max=1 E1 Cable	See Configuration Note-6
HP MSR 1-port Fractional SIC Module	JD538A
<ul style="list-style-type: none">• None	See Configuration Note-7
HP MSR 2-port Fractional E1 SIC Module	JF842A
<ul style="list-style-type: none">• None	See Configuration Note-12
HP MSR 1-port Enhanced Serial SIC Mod	JD557A
<ul style="list-style-type: none">• None	See Configuration Note-8
HP A-MSR 1-port ADSL over POTS SIC Module	JD537A
<ul style="list-style-type: none">• None	
HP MSR 1-port ISDN-S/T SIC Module	JD571A

Configuration

<ul style="list-style-type: none"> • None 	
HP A-MSR 8-port Async Serial SIC Module <ul style="list-style-type: none"> • Must select 1 8AS Communication Cable (min=1 \ max=1 cable) 	JF281A See Configuration Note~9
HP 802.11b/g/n Wireless AP SIC Module <ul style="list-style-type: none"> • None 	JF819A
HP MSR 802.11b/g/n Wless AP SIC Mod (NA) <ul style="list-style-type: none"> • None 	JG211A
HP MSR 1p 8-wire G.SHDSL (RJ45) DSIC Mod <ul style="list-style-type: none"> • None 	JG191A See Configuration Note~2
HP MSR 1-port ADSL over ISDN SIC Module <ul style="list-style-type: none"> • None 	JG056B
HP MSR 16-port Async Serial SIC Module <ul style="list-style-type: none"> • Must select 4 HP X260 mini D-28/4-RJ45 0.3m Rtr Cables (min=4 \ max=4 cables) 	JG186A See Configuration Note~9, 10
HP A-MSR 4-port FXS/1-port FXO DSIC Mod <ul style="list-style-type: none"> • None 	JG189A See Configuration Note~2
HP A-MSR HSPA/WCDMA SIC Module <ul style="list-style-type: none"> • None 	JG187A
HP MSR 4G LTE SIC Mod for Verizon <ul style="list-style-type: none"> • None 	JG742A See Configuration Note~13
HP MSR 4G LTE SIC Mod for ATT <ul style="list-style-type: none"> • None 	JG743A See Configuration Note~13
HP MSR 4G LTE SIC Mod for Global <ul style="list-style-type: none"> • None 	JG744A See Configuration Note~13

Configuration

Configuration Rules²

Note 1	These Modules are NOT supported on the following routers ²	
	HP A-MSR20-13 Router	JD240A
	HP A-MSR20-13-W Router	JF808A
	HP A-MSR20-13-W Router (NA)	JF210A
Note 2	This Module takes up one slot on this router. (Special Slot)	
Note 4	The following Transceivers install into this Module ²	
	HP X110 100M SFP LC LH40 Transceiver	JD090A
	HP X110 100M SFP LC LH80 Transceiver	JD091A
	HP X115 100M SFP LC FX Transceiver	JD102B
	HP X110 100M SFP LC LX Transceiver	JD120B
Note 5	The following Transceivers install into this Module ²	
	HP X125 1G SFP LC LH70 Transceiver	JD063B
	HP X120 1G SFP LC LH40 1550nm Transceiver	JD062A
	HP X125 1G SFP LC LH40 1310nm Transceiver	JD061A
	HP X120 1G SFP LC LH100 Transceiver	JD103A
	HP X120 1G SFP LC SX Transceiver	JD118B
	HP X120 1G SFP LC LX Transceiver	JD119B
Note 6	The following E1 Cables install into this Module ²	
	HP X260 E1 (2) BNC 75 ohm 3m Router Cable	JD175A
	HP X260 E1 BNC 20m Router Cable	JD514A
	HP X260 E1 2 BNC 75 ohm 40m Router Cable	JD516A
Note 7	The following T1 Cables install into this Module ²	
	T1 Cable RJ45/RJ45-3m	JD518A
Note 8	The following Cables install into this Module ²	
	HP X200 V.24 DTE 3m Serial Port Cable	JD519A
	HP X200 V.24 DCE 3m Serial Port Cable	JD521A
	HP X200 V.35 DTE 3m Serial Port Cable	JD523A
	HP X200 V.35 DCE 3m Serial Port Cable	JD525A
	HP X200 X.21 DTE 3m Serial Port Cable	JD527A
	HP X200 X.21 DCE 3m Serial Port Cable	JD529A
	HP X260 RS449 3m DTE Serial Port Cable	JF825A
	HP X260 RS449 3m DCE Serial Port Cable	JF826A

Configuration

HP X260 RS530 3m DTE Serial Port Cable	JF827A
HP X260 RS530 3m DCE Serial Port Cable	JF828A

Note 9 If this module is selected Then 1 JD642A - HP X260 SIC-8AS RJ45 0.28m Router Cable is required.

Note 10 If this module is selected Then 4 - JG263A HP X260 mini D-28/4-RJ45 0.3m Rtr Cable are required to be on the same order.

Note 11 The following E1 Cables install into this Module=

HP X260 E1 RJ45 3m Router Cable	JD509A
HP X260 E1 RJ45 20m Router Cable	JD517A

Note 12 The following 2E1 Cables install into this Module=

HP X260 2E1 BNC 3m Router Cable	JD643A
---------------------------------	--------

Note 13 The following Antenna Cables install into this Module=

HP MSR 3G RF 2.8m Antenna Cable	JG522A
HP MSR 3G RF 6m Antenna Cable	JG666A
HP MSR 3G RF 15m Antenna Cable	JG667A

Voice Processing Modules

JD431A, JF239A, JF241A, JF806A, JF807A, JG209A, JF236A, JF809A, JF237A, JF238A, JF817A Only - System (std 0 // max 2) User Selection (min 0 // max 1)

HP MSR 32-channel Voice Processor Module	JD598A
HP MSR 24-channel Voice Processor Module	JD599A
HP MSR 16-channel Voice Processor Module	JD600A
HP MSR 8-channel Voice Processor Module	JD601A

Transceivers

SFP Transceivers

HP X115 100M SFP LC FX Transceiver	JD102B
HP X110 100M SFP LC LH40 Transceiver	JD120B

Configuration

HP X110 100M SFP LC LH80 Transceiver	JD091A
HP X120 1G SFP LC SX Transceiver	JD118B
HP X120 1G SFP LC LX Transceiver	JD119B
HP X120 1G SFP LC LH40 1550nm Transceiver	JD062A
HP X110 100M SFP LC LH40 Transceiver	JD090A
HP X125 1G SFP LC LH40 1310nm Transceiver	JD061A
HP X125 1G SFP LC LH70 Transceiver	JD063B
HP X120 1G SFP RJ45 T Transceiver	JD089B
HP X120 1G SFP LC BX 10-D Transceiver	JD099B

Cables

HP X260 mini D-28/4-RJ45 0.3m Rtr Cable	JG263A
HP X200 V.24 DTE 3m Serial Port Cable	JD519A
HP X200 V.24 DCE 3m Serial Port Cable	JD521A
HP X200 V.35 DTE 3m Serial Port Cable	JD523A
HP X200 V.35 DCE 3m Serial Port Cable	JD525A
HP X200 X.21 DTE 3m Serial Port Cable	JD527A
HP X200 X.21 DCE 3m Serial Port Cable	JD529A
HP X260 RS449 3m DTE Serial Port Cable	JF825A
HP X260 RS449 3m DCE Serial Port Cable	JF826A
HP X260 RS530 3m DTE Serial Port Cable	JF827A
HP X260 RS530 3m DCE Serial Port Cable	JF828A



Configuration

HP X260 Auxiliary Router Cable	JD508A
HP X260 E1 RJ45 3m Router Cable	JD509A
HP X260 E1 RJ45 20m Router Cable	JD517A
HP X260 E1 (2) BNC 75 ohm 3m Rtr Cable	JD175A
HP X260 E1 BNC 20m Router Cable	JD514A
HP X260 E1/2 BNC 75 ohm 40m Router Cable	JD516A
HP X260 E1 RJ45 BNC 75-120 ohm Conversion Router Cable	JD511A
HP X260 2E1 BNC 3m Router Cable	JD643A
HP X260 T1 Router Cable	JD518A
HP X260 T1 Voice Router Cable	JD535A
HP X260 T3/E3 Router Cable	JD531A
HP X260 E3-30 E3/T3 Router Cable	JD533A
HP X260 E1 4-port IMA Router Cable	JD638A
HP X260 8E1 BNC 75 ohm 3m Router Cable	JD512A
HP X260 SIC-8AS RJ45 0.28m Router Cable	JD642A
HP X200 Transit Plug D25F MP8(S) Single Cable	JD636A
HP X200 Transit Cable RJ45 0.5m Single Cable	JD641A

Remarks

The following cable is used for RJ45 BNC Conversion -
HP X260 E1 RJ45 BNC 75-120 ohm Conversion Router Cable

JD511A

Router Options



Configuration

Antenna Cables

System (std 0 // max 2) User Selection (min 0 // max 2) per SIC Module (JG742A, JG743A, JG744A)

HP MSR 3G RF 2.8m Antenna Cable JG522A

HP MSR 3G RF 6m Antenna Cable JG666A

HP MSR 3G RF 15m Antenna Cable JG667A

Compact Flash cards

System (std 0 // max 1) User Selection (min 0 // max 1)

HP 7500 1G Compact Flash Card JC684A

HP 7500 512M Compact Flash Card JC685A

HP 7500 256MB Compact Flash Card JC686A

Mount Angle Components

System (std 0 // max 1) User Selection (min 0 // max 1)

HP A3100/E4210-16/-8 POE Rack Mount Kit JD323A

Technical Specifications

HP MSR20-10 Router (JD431A)

Ports	1 SIC slot 1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX) [†] Duplex=half or full 4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX) [†] Duplex=half or full
Physical characteristics	Dimensions 11.81(w) x 9.45(d) x 1.74(h) in. (30 x 24 x 4.42 cm) (1U height) Weight 6.61 lb (3.0 kg)
Memory and processor	Processor RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
Mounting	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.
Performance	Throughput up to 160 Kpps (64-byte packets) Routing table size 10000 entries (IPv4), 10000 entries (IPv6)
Environment	Operating temperature 32°F to 104°F (0°C to 40°C) Operating relative humidity 5% to 90%, noncondensing Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C) Nonoperating/Storage relative humidity 5% to 90%, noncondensing
Electrical characteristics	Maximum heat dissipation 85 BTU/hr (89.68 kJ/hr) Voltage 100-240 VAC Maximum power rating 25 W Frequency 50/60 Hz Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1 CAN/CSA 22.2 No. 60950-1 AS/NZS 60950 EN 60825-1 Safety of Laser Products-Part 1 EN 60825-2 Safety of Laser Products-Part 2 IEC 60950-1 EN 60950-1 CAN/CSA-C22.2 No. 60950-1-03 EN 60950-1/A11 FDA 21 CFR Subchapter J

Technical Specifications

Emissions	EN 55022 Class B†ICES-003 Class B†ANSI C63.4 2003†ETSI EN 300 386 V1.3.3†EN 61000-4-2†EN 61000-4-3†EN 61000-4-4†EN 61000-4-5†EN 61000-4-6†EN 61000-3-2†2006†EN 61000-3-3†1995 +A1†2001+A2†2005†EMC Directive 2004/108/EC†EN 55024†1998+ A1†2001 + A2†2003†EN 61000-4-11†2004†EN 61000-4-8†2001†AS/NZS CISPR 22 Class B†FCC (CFR 47, Part 15) Class B
Telecom	FCC part 68†CS-03
Management	IMC - Intelligent Management Center†command-line interface†Web browser†out-of-band management (serial RS-232C)†out-of-band management (DB-9 serial port console)†SNMP Manager†Telnet†RMON1†FTP†IEEE 802.3 Ethernet MIB
Notes	The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Weight is with no optional modules installed.
Services	<p>3-year, parts only, global next-day advance exchange (UW075E)</p> <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E)</p> <p>3-year, 24x7 SW phone support, software updates (UW012E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR554E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E)</p> <p>4-year, 24x7 SW phone support, software updates (UW013E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)</p> <p>5-year, 24x7 SW phone support, software updates (UW014E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UW079E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UW080E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UW081E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR558E)</p> <p>1-year, 24x7 software phone support, software updates (HR557E)</p>

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP MSR20-11 Router (JF239A)

Ports	<p>1 SIC slot</p> <p>1 Serial port</p> <p>1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX)† Duplex†half or full</p>
--------------	--

Technical Specifications

	4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX)† Duplex=half or full
Physical characteristics	<p>Dimensions 11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)</p> <p>Weight 6.61 lb (3 kg)</p>
Memory and processor	Processor RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
Mounting	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.
Performance	<p>Throughput up to 160 Kpps (64-byte packets)</p> <p>Routing table size 10000 entries (IPv4), 10000 entries (IPv6)</p>
Environment	<p>Operating temperature 32°F to 104°F (0°C to 40°C)</p> <p>Operating relative humidity 5% to 95%, noncondensing</p> <p>Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)</p> <p>Nonoperating/Storage relative humidity 5% to 90%, noncondensing</p>
Electrical characteristics	<p>Maximum heat dissipation 85 BTU/hr (89.68 kJ/hr)</p> <p>Voltage 100-240 VAC</p> <p>Maximum power rating 25 W</p> <p>Frequency 50/60 Hz</p> <p>Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p>
Safety	<p>UL 60950-1</p> <p>CAN/CSA 22.2 No. 60950-1</p> <p>AS/NZS 60950</p> <p>EN 60825-1 Safety of Laser Products-Part 1</p> <p>EN 60825-2 Safety of Laser Products-Part 2</p> <p>IEC 60950-1</p> <p>EN 60950-1</p> <p>CAN/CSA-C22.2 No. 60950-1-03</p> <p>EN 60950-1/A11</p> <p>FDA 21 CFR Subchapter J</p>
Emissions	<p>EN 55022 Class B†ICES-003 Class B†ANSI C63.4 2003†ETSI EN 300 386 V1.3.3†EN 61000-4-2†EN 61000-4-3†EN 61000-4-4†EN 61000-4-5†EN 61000-4-6†EN 61000-3-2†2006†EN 61000-3-3†1995 +A1†2001 +A2†2005†EMC Directive 2004/108/EC†EN 55024†1998+ A1†2001 + A2†2003†EN 61000-4-11†2004†EN 61000-4-8†2001†AS/NZS CISPR 22 Class B†FCC (CFR 47, Part 15) Class B</p>
Telecom	FCC part 68†CS-03

Technical Specifications

Management	IMC - Intelligent Management Center [†] command-line interface [†] Web browser [†] out-of-band management (serial RS-232C) [†] out-of-band management (DB-9 serial port console) [†] SNMP Manager [†] Telnet [†] RMON1 [†] FTP [†] IEEE 802.3 Ethernet MIB
Notes	The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Weight is with no optional modules installed.
Services	<p>3-year, parts only, global next-day advance exchange (UW075E)</p> <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E)</p> <p>3-year, 24x7 SW phone support, software updates (UW012E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR554E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E)</p> <p>4-year, 24x7 SW phone support, software updates (UW013E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)</p> <p>5-year, 24x7 SW phone support, software updates (UW014E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UW079E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UW080E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UW081E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR558E)</p> <p>1-year, 24x7 software phone support, software updates (HR557E)</p>

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP MSR20-12 Router (JF241A)

Ports	1 SIC slot
	1 E1 port
	1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX) [†] Duplex [†] half or full
	4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX) [†] Duplex [†] half or full
Physical characteristics	Dimensions 11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)
	Weight 6.61 lb (3.0 kg)

Technical Specifications

Memory and processor	Processor	RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
Mounting		Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.
Performance	Throughput	up to 160 Kpps (64-byte packets)
	Routing table size	10000 entries (IPv4), 10000 entries (IPv6)
Environment	Operating temperature	32°F to 104°F (0°C to 40°C)
	Operating relative humidity	5% to 90%, noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 90%, noncondensing
Electrical characteristics	Maximum heat dissipation	85 BTU/hr (89.68 kJ/hr)
	Voltage	100-240 VAC
	Maximum power rating	25 W
	Frequency	50/60 Hz
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety		UL 60950-1 CAN/CSA 22.2 No. 60950-1 AS/NZS 60950 EN 60825-1 Safety of Laser Products-Part 1 EN 60825-2 Safety of Laser Products-Part 2 IEC 60950-1 EN 60950-1 CAN/CSA-C22.2 No. 60950-1-03 EN 60950-1/A11 FDA 21 CFR Subchapter J
Emissions		EN 55022 Class B [†] ICES-003 Class B [†] ANSI C63.4 2003 [†] ETSI EN 300 386 V1.3.3 [†] EN 61000-4-2 [†] EN 61000-4-3 [†] EN 61000-4-4 [†] EN 61000-4-5 [†] EN 61000-4-6 [†] EN 61000-3-2 [‡] 2006 [†] EN 61000-3-3 [‡] 1995 +A1 [‡] 2001+A2 [‡] 2005 [†] EMC Directive 2004/108/EC [†] EN 55024 [‡] 1998+ A1 [‡] 2001 + A2 [‡] 2003 [†] EN 61000-4-11 [‡] 2004 [†] EN 61000-4-8 [‡] 2001 [†] AS/NZS CISPR 22 Class B [†] FCC (CFR 47, Part 15) Class B
Telecom		FCC part 68 [†] CS-03
Management		IMC - Intelligent Management Center [†] command-line interface [†] Web browser [†] out-of-band management (serial RS-232C) [†] out-of-band management (DB-9 serial port console) [†] SNMP Manager [†] Telnet [†] RMON1 [†] FTP [†] IEEE 802.3 Ethernet MIB
Notes		The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Height does not include antennas on wireless models [†] weight is with no optional modules installed.

Technical Specifications

Services

- 3-year, parts only, global next-day advance exchange (UW075E)
- 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E)
- 3-year, 24x7 SW phone support, software updates (UW012E)
- 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR554E)
- 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E)
- 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E)
- 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E)
- 4-year, 24x7 SW phone support, software updates (UW013E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)
- 5-year, 24x7 SW phone support, software updates (UW014E)
- 3 Yr 6 hr Call-to-Repair Onsite (UW079E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW080E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW081E)
- 1-year, 6 hour Call-To-Repair Onsite for hardware (HR558E)
- 1-year, 24x7 software phone support, software updates (HR557E)

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP MSR20-12-W Router (JF807A)

Ports

- 1 SIC slot
- 1 E1 port
- 1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX)[‡]
Duplex=half or full
- 4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX)[‡]
Duplex=half or full

AP characteristics

- Radios** Single (b/g)
- Radio operation modes** Client access
- AP operation modes** Autonomous
- Wi-Fi Alliance Certification*** b/g Wi-Fi Certified

* HP access points and access devices are Wi-Fi Certified, providing our customers with the assurance that these products have met and passed the rigorous interoperability testing performed by the Wi-Fi Alliance Organization. See the Specifications section of this series for more information.

Technical Specifications

Physical characteristics	Dimensions	11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)
	Weight	6.61 lb (3.0 kg)
Memory and processor	Processor	RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
Mounting	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.	
Performance	Throughput	up to 160 Kpps (64-byte packets)
	Routing table size	10000 entries (IPv4), 10000 entries (IPv6)
	Operating temperature	32°F to 104°F (0°C to 40°C)
Environment	Operating relative humidity	5% to 90%, noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 90%, noncondensing
Electrical characteristics	Maximum heat dissipation	85 BTU/hr (89.68 kJ/hr)
	Voltage	100-240 VAC
	Maximum power rating	25 W
	Frequency	50/60 Hz
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1 CAN/CSA 22.2 No. 60950-1 AS/NZS 60950 EN 60825-1 Safety of Laser Products-Part 1 EN 60825-2 Safety of Laser Products-Part 2 IEC 60950-1 EN 60950-1 CAN/CSA-C22.2 No. 60950-1-03 EN 60950-1/A11 FDA 21 CFR Subchapter J	
Emissions	EN 55022 Class B†ICES-003 Class B†ANSI C63.4 2003†ETSI EN 300 386 V1.3.3†EN 61000-4-2†EN 61000-4-3†EN 61000-4-4†EN 61000-4-5†EN 61000-4-6†EN 61000-3-2†2006†EN 61000-3-3†1995 +A1†2001+A2†2005†EMC Directive 2004/108/EC†EN 55024†1998+ A1†2001 + A2†2003†EN 61000-4-11†2004†EN 61000-4-8†2001†AS/NZS CISPR 22 Class B†FCC (CFR 47, Part 15) Class B	
Telecom	FCC part 68†CS-03	
Management	IMC - Intelligent Management Center†command-line interface†Web browser†out-of-band management (serial RS-232C)†out-of-band management (DB-9 serial port console)†SNMP Manager†Telnet†RMON1†FTP†IEEE 802.3 Ethernet MIB	

Technical Specifications

Notes	The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Height does not include antennas on wireless models [†] weight is with no optional modules installed.
Services	<p>3-year, parts only, global next-day advance exchange (UW075E)</p> <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E)</p> <p>3-year, 24x7 SW phone support, software updates (UW012E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR554E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E)</p> <p>4-year, 24x7 SW phone support, software updates (UW013E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)</p> <p>5-year, 24x7 SW phone support, software updates (UW014E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UW079E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UW080E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UW081E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR558E)</p> <p>1-year, 24x7 software phone support, software updates (HR557E)</p>

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP MSR20-12-T Router (JF806A)

Ports	<p>1 SIC slot</p> <p>1 T1 port</p> <p>1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX)[†] Duplex[†]half or full</p> <p>4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX)[†] Duplex[†]half or full</p>
Physical characteristics	<p>Dimensions 11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)</p> <p>Weight 6.61 lb (3 kg)</p>
Memory and processor	Processor RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
Mounting	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.

Technical Specifications

Performance	Throughput	up to 160 Kpps (64-byte packets)
	Routing table size	10000 entries (IPv4), 10000 entries (IPv6)
Environment	Operating temperature	32°F to 104°F (0°C to 40°C)
	Operating relative humidity	5% to 90%, noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 90%, noncondensing
Electrical characteristics	Maximum heat dissipation	85 BTU/hr (89.68 kJ/hr)
	Voltage	100-240 VAC
	Maximum power rating	25 W
	Frequency	50/60 Hz
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety		UL 60950-1 CAN/CSA 22.2 No. 60950-1 AS/NZS 60950 EN 60825-1 Safety of Laser Products-Part 1 EN 60825-2 Safety of Laser Products-Part 2 IEC 60950-1 EN 60950-1 CAN/CSA-C22.2 No. 60950-1-03 EN 60950-1/A11 FDA 21 CFR Subchapter J
Emissions		EN 55022 Class B ⁺ ICES-003 Class B ⁺ ANSI C63.4 2003 ⁺ ETSI EN 300 386 V1.3.3 ⁺ EN 61000-4-2 ⁺ EN 61000-4-3 ⁺ EN 61000-4-4 ⁺ EN 61000-4-5 ⁺ EN 61000-4-6 ⁺ EN 61000-3-2 ⁺ 2006 ⁺ EN 61000-3-3 ⁺ 1995 ⁺ A1 ⁺ 2001 ⁺ A2 ⁺ 2005 ⁺ EMC Directive 2004/108/EC ⁺ EN 55024 ⁺ 1998 ⁺ A1 ⁺ 2001 ⁺ + A2 ⁺ 2003 ⁺ EN 61000-4-11 ⁺ 2004 ⁺ EN 61000-4-8 ⁺ 2001 ⁺ AS/NZS CISPR 22 Class B ⁺ FCC (CFR 47, Part 15) Class B
Telecom		FCC part 68 ⁺ CS-03
Management		IMC - Intelligent Management Center ⁺ command-line interface ⁺ Web browser ⁺ out-of-band management (serial RS-232C) ⁺ out-of-band management (DB-9 serial port console) ⁺ SNMP Manager ⁺ Telnet ⁺ RMON1 ⁺ FTP ⁺ IEEE 802.3 Ethernet MIB
Notes		The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Height does not include antennas on wireless models ⁺ weight is with no optional modules installed.
Services		3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E)

Technical Specifications

- 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E)
- 3-year, 24x7 SW phone support, software updates (UW012E)
- 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR554E)
- 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E)
- 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E)
- 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E)
- 4-year, 24x7 SW phone support, software updates (UW013E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)
- 5-year, 24x7 SW phone support, software updates (UW014E)
- 3 Yr 6 hr Call-to-Repair Onsite (UW079E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW080E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW081E)
- 1-year, 6 hour Call-To-Repair Onsite for hardware (HR558E)
- 1-year, 24x7 software phone support, software updates (HR557E)

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP MSR20-12-T-W Router (NA) (JG209A)

Ports	1 SIC slot
	1 T1 port
	1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX) [‡] Duplex=half or full
	4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX) [‡] Duplex=half or full

AP characteristics	Radios	Single (b/g)
	Radio operation modes	Client access
	AP operation modes	Autonomous
	Wi-Fi Alliance Certification*	b/g Wi-Fi Certified

* HP access points and access devices are Wi-Fi Certified, providing our customers with the assurance that these products have met and passed the rigorous interoperability testing performed by the Wi-Fi Alliance Organization. See the Specifications section of this series for more information.

Physical characteristics	Dimensions	11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)
	Weight	6.79 lb (3.08 kg)
Memory and processor	Processor	RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash

Technical Specifications

Mounting	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.	
Performance	Throughput	up to 160 Kpps (64-byte packets)
	Routing table size	10000 entries (IPv4), 10000 entries (IPv6)
Environment	Operating temperature	32°F to 104°F (0°C to 40°C)
	Operating relative humidity	5% to 90%, noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 90%, noncondensing
Electrical characteristics	Maximum heat dissipation	85 BTU/hr (89.68 kJ/hr)
	Voltage	100-240 VAC
	Maximum power rating	25 W
	Frequency	50/60 Hz
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1 CAN/CSA 22.2 No. 60950-1 AS/NZS 60950 EN 60825-1 Safety of Laser Products-Part 1 EN 60825-2 Safety of Laser Products-Part 2 IEC 60950-1 EN 60950-1 CAN/CSA-C22.2 No. 60950-1-03 EN 60950-1/A11 FDA 21 CFR Subchapter J	
Emissions	EN 55022 Class B†ICES-003 Class B†ANSI C63.4 2003†ETSI EN 300 386 V1.3.3†EN 61000-4-2†EN 61000-4-3†EN 61000-4-4†EN 61000-4-5†EN 61000-4-6†EN 61000-3-2†2006†EN 61000-3-3†1995 +A1†2001 +A2†2005†EMC Directive 2004/108/EC†EN 55024†1998+ A1†2001 + A2†2003†EN 61000-4-11†2004†EN 61000-4-8†2001†AS/NZS CISPR 22 Class B†FCC (CFR 47, Part 15) Class B	
Telecom	FCC part 68†CS-03	
Management	IMC - Intelligent Management Center†command-line interface†Web browser†out-of-band management (serial RS-232C)†out-of-band management (DB-9 serial port console)†SNMP Manager†Telnet†RMON1†FTP†IEEE 802.3 Ethernet MIB	
Notes	The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Height does not include antennas on wireless models†weight is with no optional modules installed.	
Services	3-year, parts only, global next-day advance exchange (UW075E)	

Technical Specifications

- 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E)
- 3-year, 24x7 SW phone support, software updates (UW012E)
- 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR554E)
- 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E)
- 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E)
- 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E)
- 4-year, 24x7 SW phone support, software updates (UW013E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)
- 5-year, 24x7 SW phone support, software updates (UW014E)
- 3 Yr 6 hr Call-to-Repair Onsite (UW079E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW080E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW081E)

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP MSR20-13 Router (JF240A)

Ports	<ul style="list-style-type: none"> 1 SIC slot 1 RJ-11 4-wire G.shdsl port 1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX)[‡] Duplex=half or full 4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX)[‡] Duplex=half or full 						
Physical characteristics	<table border="0"> <tr> <td style="vertical-align: top;">Dimensions</td> <td>11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)</td> </tr> <tr> <td style="vertical-align: top;">Weight</td> <td>6.61 lb (3.0 kg)</td> </tr> </table>	Dimensions	11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)	Weight	6.61 lb (3.0 kg)		
Dimensions	11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)						
Weight	6.61 lb (3.0 kg)						
Memory and processor	<table border="0"> <tr> <td style="vertical-align: top;">Processor</td> <td>RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash</td> </tr> </table>	Processor	RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash				
Processor	RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash						
Mounting	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.						
Performance	<table border="0"> <tr> <td style="vertical-align: top;">Throughput</td> <td>up to 160 Kpps (64-byte packets)</td> </tr> <tr> <td style="vertical-align: top;">Routing table size</td> <td>10000 entries (IPv4), 10000 entries (IPv6)</td> </tr> </table>	Throughput	up to 160 Kpps (64-byte packets)	Routing table size	10000 entries (IPv4), 10000 entries (IPv6)		
Throughput	up to 160 Kpps (64-byte packets)						
Routing table size	10000 entries (IPv4), 10000 entries (IPv6)						
Environment	<table border="0"> <tr> <td style="vertical-align: top;">Operating temperature</td> <td>32°F to 104°F (0°C to 40°C)</td> </tr> <tr> <td style="vertical-align: top;">Operating relative humidity</td> <td>5%% to 90%%, noncondensing</td> </tr> <tr> <td style="vertical-align: top;">Nonoperating/Storage temperature</td> <td>-40°F to 158°F (-40°C to 70°C)</td> </tr> </table>	Operating temperature	32°F to 104°F (0°C to 40°C)	Operating relative humidity	5%% to 90%%, noncondensing	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
Operating temperature	32°F to 104°F (0°C to 40°C)						
Operating relative humidity	5%% to 90%%, noncondensing						
Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)						

Technical Specifications

	Nonoperating/Storage relative humidity	5% to 90%, noncondensing
Electrical characteristics	Maximum heat dissipation	85 BTU/hr (89.68 kJ/hr)
	Voltage	100-240 VAC
	Maximum power rating	25 W
	Frequency	50/60 Hz
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety		<ul style="list-style-type: none"> UL 60950-1 CAN/CSA 22.2 No. 60950-1 AS/NZS 60950 EN 60825-1 Safety of Laser Products-Part 1 EN 60825-2 Safety of Laser Products-Part 2 IEC 60950-1 EN 60950-1 CAN/CSA-C22.2 No. 60950-1-03 EN 60950-1/A11 FDA 21 CFR Subchapter J
Emissions		<ul style="list-style-type: none"> EN 55022 Class B†ICES-003 Class B†ANSI C63.4 2003†ETSI EN 300 386 V1.3.3†EN 61000-4-2†EN 61000-4-3†EN 61000-4-4†EN 61000-4-5†EN 61000-4-6†EN 61000-3-2†2006†EN 61000-3-3†1995 +A1†2001 +A2†2005†EMC Directive 2004/108/EC†EN 55024†1998+ A1†2001 + A2†2003†EN 61000-4-11†2004†EN 61000-4-8†2001†AS/NZS CISPR 22 Class B†FCC (CFR 47, Part 15) Class B
Telecom		FCC part 68†CS-03
Management		IMC - Intelligent Management Center†command-line interface†Web browser†out-of-band management (serial RS-232C)†out-of-band management (DB-9 serial port console)†SNMP Manager†Telnet†RMON1†FTP†IEEE 802.3 Ethernet MIB
Notes		The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Height does not include antennas on wireless models†weight is with no optional modules installed.
Services		<ul style="list-style-type: none"> 3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E) 3-year, 24x7 SW phone support, software updates (UW012E) 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR554E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E)

Technical Specifications

- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E)
- 4-year, 24x7 SW phone support, software updates (UW013E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)
- 5-year, 24x7 SW phone support, software updates (UW014E)
- 3 Yr 6 hr Call-to-Repair Onsite (UW079E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW080E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW081E)
- 1-year, 6 hour Call-To-Repair Onsite for hardware (HR558E)
- 1-year, 24x7 software phone support, software updates (HR557E)

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP MSR20-13-W Router (JF808A)

Ports	1 SIC slot								
	1 RJ-11 4-wire G.shdsl port								
	1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX) [†] Duplex [†] half or full								
	4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX) [†] Duplex [†] half or full								
AP characteristics	<table border="0"> <tr> <td>Radios</td> <td>Single (b/g)</td> </tr> <tr> <td>Radio operation modes</td> <td>Client access</td> </tr> <tr> <td>AP operation modes</td> <td>Autonomous</td> </tr> <tr> <td>Wi-Fi Alliance Certification*</td> <td>b/g Wi-Fi Certified</td> </tr> </table> <p>* HP access points and access devices are Wi-Fi Certified, providing our customers with the assurance that these products have met and passed the rigorous interoperability testing preformed by the Wi-Fi Alliance Organization. See the Specifications section of this series for more information.</p>	Radios	Single (b/g)	Radio operation modes	Client access	AP operation modes	Autonomous	Wi-Fi Alliance Certification*	b/g Wi-Fi Certified
Radios	Single (b/g)								
Radio operation modes	Client access								
AP operation modes	Autonomous								
Wi-Fi Alliance Certification*	b/g Wi-Fi Certified								
Physical characteristics	<table border="0"> <tr> <td>Dimensions</td> <td>11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)</td> </tr> <tr> <td>Weight</td> <td>6.61 lb (3.0 kg)</td> </tr> </table>	Dimensions	11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)	Weight	6.61 lb (3.0 kg)				
Dimensions	11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)								
Weight	6.61 lb (3.0 kg)								
Memory and processor	Processor RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash								
Mounting	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.								
Performance	<table border="0"> <tr> <td>Throughput</td> <td>up to 160 Kpps (64-byte packets)</td> </tr> <tr> <td>Routing table size</td> <td>10000 entries (IPv4), 10000 entries (IPv6)</td> </tr> </table>	Throughput	up to 160 Kpps (64-byte packets)	Routing table size	10000 entries (IPv4), 10000 entries (IPv6)				
Throughput	up to 160 Kpps (64-byte packets)								
Routing table size	10000 entries (IPv4), 10000 entries (IPv6)								
Environment	<table border="0"> <tr> <td>Operating temperature</td> <td>32°F to 104°F (0°C to 40°C)</td> </tr> <tr> <td>Operating relative humidity</td> <td>5% to 95%, noncondensing</td> </tr> </table>	Operating temperature	32°F to 104°F (0°C to 40°C)	Operating relative humidity	5% to 95%, noncondensing				
Operating temperature	32°F to 104°F (0°C to 40°C)								
Operating relative humidity	5% to 95%, noncondensing								

Technical Specifications

	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 95%, noncondensing
Electrical characteristics	Maximum heat dissipation	85 BTU/hr (89.68 kJ/hr)
	Voltage	100-240 VAC
	Maximum power rating	25 W
	Frequency	50/60 Hz
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety		<ul style="list-style-type: none"> UL 60950-1 CAN/CSA 22.2 No. 60950-1 AS/NZS 60950 EN 60825-1 Safety of Laser Products-Part 1 EN 60825-2 Safety of Laser Products-Part 2 IEC 60950-1 EN 60950-1 CAN/CSA-C22.2 No. 60950-1-03 EN 60950-1/A11 FDA 21 CFR Subchapter J
Emissions		<ul style="list-style-type: none"> EN 55022 Class B†ICES-003 Class B†ANSI C63.4 2003†ETSI EN 300 386 V1.3.3†EN 61000-4-2†EN 61000-4-3†EN 61000-4-4†EN 61000-4-5†EN 61000-4-6†EN 61000-3-2†2006†EN 61000-3-3†1995 +A1†2001 +A2†2005†EMC Directive 2004/108/EC†EN 55024†1998+ A1†2001 + A2†2003†EN 61000-4-11†2004†EN 61000-4-8†2001†AS/NZS CISPR 22 Class B†FCC (CFR 47, Part 15) Class B
Telecom		FCC part 68†CS-03
Management		IMC - Intelligent Management Center†command-line interface†Web browser†out-of-band management (serial RS-232C)†out-of-band management (DB-9 serial port console)†SNMP Manager†Telnet†RMON1†FTP†IEEE 802.3 Ethernet MIB
Notes		The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Height does not include antennas on wireless models†weight is with no optional modules installed.
Services		<ul style="list-style-type: none"> 3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E) 3-year, 24x7 SW phone support, software updates (UW012E) 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR554E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support

Technical Specifications

- (HR556E)
- 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E)
- 4-year, 24x7 SW phone support, software updates (UW013E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)
- 5-year, 24x7 SW phone support, software updates (UW014E)
- 3 Yr 6 hr Call-to-Repair Onsite (UW079E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW080E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW081E)
- 1-year, 6 hour Call-To-Repair Onsite for hardware (HR558E)
- 1-year, 24x7 software phone support, software updates (HR557E)

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP MSR20-13-W Router (NA) (JG210A)

Ports	<ul style="list-style-type: none"> 1 SIC slot 1 T1 port 1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX)[‡] Duplex=half or full 4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX)[‡] Duplex=half or full 	
AP characteristics	Radios	Single (b/g)
	Radio operation modes	Client access
	AP operation modes	Autonomous
	Wi-Fi Alliance Certification*	b/g Wi-Fi Certified
	<p>* HP access points and access devices are Wi-Fi Certified, providing our customers with the assurance that these products have met and passed the rigorous interoperability testing performed by the Wi-Fi Alliance Organization. See the Specifications section of this series for more information.</p>	
Physical characteristics	Dimensions	11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)
	Weight	7.01 lb (3.18 kg)
Memory and processor	Processor	RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
Mounting	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.	
Performance	Throughput	up to 160 Kpps (64-byte packets)
	Routing table size	10000 entries (IPv4), 10000 entries (IPv6)
Environment	Operating temperature	32°F to 104°F (0°C to 40°C)

Technical Specifications

	Operating relative humidity	5% to 95%, noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 95%, noncondensing
Electrical characteristics	Maximum heat dissipation	85 BTU/hr (89.68 kJ/hr)
	Voltage	100-240 VAC
	Maximum power rating	25 W
	Frequency	50/60 Hz
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety		<ul style="list-style-type: none"> UL 60950-1 CAN/CSA 22.2 No. 60950-1 AS/NZS 60950 EN 60825-1 Safety of Laser Products-Part 1 EN 60825-2 Safety of Laser Products-Part 2 IEC 60950-1 EN 60950-1 CAN/CSA-C22.2 No. 60950-1-03 EN 60950-1/A11 FDA 21 CFR Subchapter J
Emissions		<ul style="list-style-type: none"> EN 55022 Class B⁺ICES-003 Class B⁺ANSI C63.4 2003⁺ETSI EN 300 386 V1.3.3⁺EN 61000-4-2⁺EN 61000-4-3⁺EN 61000-4-4⁺EN 61000-4-5⁺EN 61000-4-6⁺EN 61000-3-2⁺2006⁺EN 61000-3-3⁺1995 +A1⁺2001+A2⁺2005⁺EMC Directive 2004/108/EC⁺EN 55024⁺1998+ A1⁺2001 + A2⁺2003⁺EN 61000-4-11⁺2004⁺EN 61000-4-8⁺2001⁺AS/NZS CISPR 22 Class B⁺FCC (CFR 47, Part 15) Class B
Telecom		FCC part 68 ⁺ CS-03
Management		IMC - Intelligent Management Center ⁺ command-line interface ⁺ Web browser ⁺ out-of-band management (Serial RS-232C) ⁺ out-of-band management (DB-9 serial port console) ⁺ SNMP Manager ⁺ Telnet ⁺ RMON1 ⁺ FTP ⁺ IEEE 802.3 Ethernet MIB
Notes		The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Height does not include antennas on wireless models ⁺ weight is with no optional modules installed.
Services		<ul style="list-style-type: none"> 3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E) 3-year, 24x7 SW phone support, software updates (UW012E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E)

Technical Specifications

- 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E)
- 4-year, 24x7 SW phone support, software updates (UW013E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)
- 5-year, 24x7 SW phone support, software updates (UW014E)
- 3 Yr 6 hr Call-to-Repair Onsite (UW079E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW080E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW081E)

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP MSR20-15-A Router (JF237A)

Ports	1 SIC slot
	1 RJ-45 ADSL2+ port
	1 Analog Modem port
	1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX)± Duplex±half or full
	4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX)± Duplex±half or full
Physical characteristics	Dimensions 11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)
	Weight 6.61 lb (3.0 kg)
Memory and processor	Processor RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
Mounting	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.
Performance	Throughput up to 160 Kpps (64-byte packets)
	Routing table size 10000 entries (IPv4), 10000 entries (IPv6)
Environment	Operating temperature 32°F to 104°F (0°C to 40°C)
	Operating relative humidity 5% to 90%, noncondensing
	Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity 5% to 90%, noncondensing
Electrical characteristics	Maximum heat dissipation 85 BTU/hr (89.68 kJ/hr)
	Voltage 100-240 VAC
	Maximum power rating 25 W

Technical Specifications

Frequency	50/60 Hz
Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.

Safety	<p>UL 60950-1 CAN/CSA 22.2 No. 60950-1 AS/NZS 60950 EN 60825-1 Safety of Laser Products-Part 1 EN 60825-2 Safety of Laser Products-Part 2 IEC 60950-1 EN 60950-1 CAN/CSA-C22.2 No. 60950-1-03 EN 60950-1/A11 FDA 21 CFR Subchapter J</p>
Emissions	<p>EN 55022 Class B+ICES-003 Class B+ANSI C63.4 2003+ETSI EN 300 386 V1.3.3+EN 61000-4-2+EN 61000-4-3+EN 61000-4-4+EN 61000-4-5+EN 61000-4-6+EN 61000-3-2+2006+EN 61000-3-3+1995 +A1+2001+A2+2005+EMC Directive 2004/108/EC+EN 55024+1998+ A1+2001 + A2+2003+EN 61000-4-11+2004+EN 61000-4-8+2001+AS/NZS CISPR 22 Class B+FCC (CFR 47, Part 15) Class B</p>
Telecom	FCC part 68+CS-03
Management	<p>IMC - Intelligent Management Center+command-line interface+Web browser+out-of-band management (Serial RS-232C)+out-of-band management (DB-9 serial port console)+SNMP Manager+Telnet+RMON1+FTP+IEEE 802.3 Ethernet MIB</p>
Notes	<p>The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Height does not include antennas on wireless models+weight is with no optional modules installed.</p>
Services	<p>3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E) 3-year, 24x7 SW phone support, software updates (UW012E) 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR554E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E) 5-year, 24x7 SW phone support, software updates (UW014E) 3 Yr 6 hr Call-to-Repair Onsite (UW079E) 4 Yr 6 hr Call-to-Repair Onsite (UW080E)</p>

Technical Specifications

5 Yr 6 hr Call-to-Repair Onsite (UW081E)
 1-year, 6 hour Call-To-Repair Onsite for hardware (HR558E)
 1-year, 24x7 software phone support, software updates (HR557E)

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP MSR20-15-A-W Router (JF809A)

Ports

- 1 SIC slot
- 1 RJ-45 ADSL2+ port
- 1 Analog Modem port
- 1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX)[‡]
Duplex=half or full
- 4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX)[‡]
Duplex=half or full

AP characteristics

- Radios** Single (b/g)
- Radio operation modes** Client access
- AP operation modes** Autonomous
- Wi-Fi Alliance Certification*** b/g Wi-Fi Certified

* HP access points and access devices are Wi-Fi Certified, providing our customers with the assurance that these products have met and passed the rigorous interoperability testing performed by the Wi-Fi Alliance Organization. See the Specifications section of this series for more information.

Physical characteristics

- Dimensions** 11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)
- Weight** 6.61 lb (3.0 kg)

Memory and processor

- Processor** RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash

Mounting Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.

Performance

- Throughput** up to 160 Kpps (64-byte packets)

Routing table size 10000 entries (IPv4), 10000 entries (IPv6)

Environment

- Operating temperature** 32°F to 104°F (0°C to 40°C)

Operating relative humidity 5% to 90%, noncondensing

Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)

Nonoperating/Storage relative humidity 5% to 90%, noncondensing

Electrical characteristics

- Maximum heat dissipation** 85 BTU/hr (89.68 kJ/hr)

Voltage 100-240 VAC

Technical Specifications

Maximum power rating	25 W
Frequency	50/60 Hz
Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.

Safety	<ul style="list-style-type: none"> UL 60950-1 CAN/CSA 22.2 No. 60950-1 AS/NZS 60950 EN 60825-1 Safety of Laser Products-Part 1 EN 60825-2 Safety of Laser Products-Part 2 IEC 60950-1 EN 60950-1 CAN/CSA-C22.2 No. 60950-1-03 EN 60950-1/A11 FDA 21 CFR Subchapter J
Emissions	<ul style="list-style-type: none"> EN 55022 Class B⁺ICES-003 Class B⁺ANSI C63.4 2003⁺ETSI EN 300 386 V1.3.3⁺EN 61000-4-2⁺EN 61000-4-3⁺EN 61000-4-4⁺EN 61000-4-5⁺EN 61000-4-6⁺EN 61000-3-2⁺2006⁺EN 61000-3-3⁺1995 +A1⁺2001+A2⁺2005⁺EMC Directive 2004/108/EC⁺EN 55024⁺1998+ A1⁺2001 + A2⁺2003⁺EN 61000-4-11⁺2004⁺EN 61000-4-8⁺2001⁺AS/NZS CISPR 22 Class B⁺FCC (CFR 47, Part 15) Class B
Telecom	<ul style="list-style-type: none"> FCC part 68⁺CS-03
Management	<ul style="list-style-type: none"> IMC - Intelligent Management Center⁺command-line interface⁺Web browser⁺out-of-band management (Serial RS-232C)⁺out-of-band management (DB-9 serial port console)⁺SNMP Manager⁺Telnet⁺RMON1⁺FTP⁺IEEE 802.3 Ethernet MIB
Notes	<ul style="list-style-type: none"> The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Height does not include antennas on wireless models⁺weight is with no optional modules installed.
Services	<ul style="list-style-type: none"> 3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E) 3-year, 24x7 SW phone support, software updates (UW012E) 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR554E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E) 4-year, 24x7 SW phone support, software updates (UW013E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)

Technical Specifications

- 5-year, 24x7 SW phone support, software updates (UW014E)
- 3 Yr 6 hr Call-to-Repair Onsite (UW079E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW080E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW081E)
- 1-year, 6 hour Call-To-Repair Onsite for hardware (HR558E)
- 1-year, 24x7 software phone support, software updates (HR557E)

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP MSR20-15-I Router (JF236A)

Ports	<ul style="list-style-type: none"> 1 SIC slot 1 RJ-45 ADSL2+ port 1 ISDN port 1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX)± Duplex±half or full 4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX)± Duplex±half or full
Physical characteristics	<ul style="list-style-type: none"> Dimensions 11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height) Weight 6.61 lb (3.0 kg)
Memory and processor	<ul style="list-style-type: none"> Processor RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
Mounting	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.
Performance	<ul style="list-style-type: none"> Throughput up to 160 Kpps (64-byte packets) Routing table size 10000 entries (IPv4), 10000 entries (IPv6)
Environment	<ul style="list-style-type: none"> Operating temperature 32°F to 104°F (0°C to 40°C) Operating relative humidity 5% to 90%, noncondensing Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C) Nonoperating/Storage relative humidity 5% to 90%, noncondensing
Electrical characteristics	<ul style="list-style-type: none"> Maximum heat dissipation 85 BTU/hr (89.68 kJ/hr) Voltage 100-240 VAC Maximum power rating 25 W Frequency 50/60 Hz

Technical Specifications

Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.

Safety	<ul style="list-style-type: none"> UL 60950-1 CAN/CSA 22.2 No. 60950-1 AS/NZS 60950 EN 60825-1 Safety of Laser Products-Part 1 EN 60825-2 Safety of Laser Products-Part 2 IEC 60950-1 EN 60950-1 CAN/CSA-C22.2 No. 60950-1-03 EN 60950-1/A11 FDA 21 CFR Subchapter J
Emissions	<ul style="list-style-type: none"> EN 55022 Class B+ICES-003 Class B+ANSI C63.4 2003+ETSI EN 300 386 V1.3.3+EN 61000-4-2+EN 61000-4-3+EN 61000-4-4+EN 61000-4-5+EN 61000-4-6+EN 61000-3-2+2006+EN 61000-3-3+1995 +A1+2001+A2+2005+EMC Directive 2004/108/EC+EN 55024+1998+ A1+2001 + A2+2003+EN 61000-4-11+2004+EN 61000-4-8+2001+AS/NZS CISPR 22 Class B+FCC (CFR 47, Part 15) Class B
Telecom	<ul style="list-style-type: none"> FCC part 68+CS-03
Management	<ul style="list-style-type: none"> IMC - Intelligent Management Center+command-line interface+Web browser+out-of-band management (serial RS-232C)+out-of-band management (DB-9 serial port console)+SNMP Manager+Telnet+RMON1+FTP+IEEE 802.3 Ethernet MIB
Notes	<p>The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Height does not include antennas on wireless models+weight is with no optional modules installed.</p>
Services	<ul style="list-style-type: none"> 3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E) 3-year, 24x7 SW phone support, software updates (UW012E) 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR554E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E) 4-year, 24x7 SW phone support, software updates (UW013E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E) 5-year, 24x7 SW phone support, software updates (UW014E) 3 Yr 6 hr Call-to-Repair Onsite (UW079E) 4 Yr 6 hr Call-to-Repair Onsite (UW080E)

Technical Specifications

5 Yr 6 hr Call-to-Repair Onsite (UW081E)
 1-year, 6 hour Call-To-Repair Onsite for hardware (HR558E)
 1-year, 24x7 software phone support, software updates (HR557E)

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP MSR20-15-I-W Router (JF238A)

Ports

- 1 SIC slot
- 1 RJ-45 ADSL2+ port
- 1 ISDN port
- 1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX)[‡]
Duplex=half or full
- 4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX)[‡]
Duplex=half or full

AP characteristics

- Radios** Single (b/g)
- Radio operation modes** Client access
- AP operation modes** Autonomous
- Wi-Fi Alliance Certification*** b/g Wi-Fi Certified

* HP access points and access devices are Wi-Fi Certified, providing our customers with the assurance that these products have met and passed the rigorous interoperability testing performed by the Wi-Fi Alliance Organization. See the Specifications section of this series for more information.

Physical characteristics

- Dimensions** 11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)
- Weight** 6.61 lb (3 kg)

Memory and processor **Processor** RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash

Mounting Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.

Performance **Throughput** up to 160 Kpps (64-byte packets)

Routing table size 10000 entries (IPv4), 10000 entries (IPv6)

Environment **Operating temperature** 32°F to 104°F (0°C to 40°C)

Operating relative humidity 5% to 90%, noncondensing

Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)

Nonoperating/Storage relative humidity 5% to 90%, noncondensing

Electrical characteristics **Maximum heat dissipation** 85 BTU/hr (89.68 kJ/hr)

Voltage 100-240 VAC

Technical Specifications

Maximum power rating	25 W
Frequency	50/60 Hz
Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.

Safety	<p>UL 60950-1 CAN/CSA 22.2 No. 60950-1 AS/NZS 60950 EN 60825-1 Safety of Laser Products-Part 1 EN 60825-2 Safety of Laser Products-Part 2 IEC 60950-1 EN 60950-1 CAN/CSA-C22.2 No. 60950-1-03 EN 60950-1/A11 FDA 21 CFR Subchapter J</p>
Emissions	<p>EN 55022 Class B⁺ICES-003 Class B⁺ANSI C63.4 2003⁺ETSI EN 300 386 V1.3.3⁺EN 61000-4-2⁺EN 61000-4-3⁺EN 61000-4-4⁺EN 61000-4-5⁺EN 61000-4-6⁺EN 61000-3-2⁺2006⁺EN 61000-3-3⁺1995 +A1⁺2001+A2⁺2005⁺EMC Directive 2004/108/EC⁺EN 55024⁺1998+ A1⁺2001 + A2⁺2003⁺EN 61000-4-11⁺2004⁺EN 61000-4-8⁺2001⁺AS/NZS CISPR 22 Class B⁺FCC (CFR 47, Part 15) Class B</p>
Telecom	FCC part 68 ⁺ CS-03
Management	<p>IMC - Intelligent Management Center⁺command-line interface⁺Web browser⁺out-of-band management (Serial RS-232C)⁺out-of-band management (DB-9 serial port console)⁺SNMP Manager⁺Telnet⁺RMON1⁺FTP⁺IEEE 802.3 Ethernet MIB</p>
Notes	The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Height does not include antennas on wireless models ⁺ weight is with no optional modules installed.
Services	<p>3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E) 3-year, 24x7 SW phone support, software updates (UW012E) 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR554E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E) 4-year, 24x7 SW phone support, software updates (UW013E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)</p>

Technical Specifications

- 5-year, 24x7 SW phone support, software updates (UW014E)
- 3 Yr 6 hr Call-to-Repair Onsite (UW079E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW080E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW081E)
- 1-year, 6 hour Call-To-Repair Onsite for hardware (HR558E)
- 1-year, 24x7 software phone support, software updates (HR557E)

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP MSR20-15 Router (JF817A)

Ports	1 SIC slot
	1 RJ-45 ADSL2+ port
	1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX) [†] Duplex=half or full
	4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX) [†] Duplex=half or full
Physical characteristics	Dimensions 11.81(w) x 9.45(d) x 1.74(h) in (30 x 24 x 4.42 cm) (1U height)
	Weight 6.61 lb (3.0 kg)
Memory and processor	Processor RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
Mounting	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.
Performance	Throughput up to 160 Kpps (64-byte packets)
	Routing table size 10000 entries (IPv4), 10000 entries (IPv6)
Environment	Operating temperature 32°F to 104°F (0°C to 40°C)
	Operating relative humidity 5% to 90%, noncondensing
	Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity 5% to 90%, noncondensing
Electrical characteristics	Maximum heat dissipation 85 BTU/hr (89.68 kJ/hr)
	Voltage 100-240 VAC
	Maximum power rating 25 W
	Frequency 50/60 Hz
	Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.

Technical Specifications

Safety	<ul style="list-style-type: none"> UL 60950-1 CAN/CSA 22.2 No. 60950-1 AS/NZS 60950 EN 60825-1 Safety of Laser Products-Part 1 EN 60825-2 Safety of Laser Products-Part 2 IEC 60950-1 EN 60950-1 CAN/CSA-C22.2 No. 60950-1-03 EN 60950-1/A11 FDA 21 CFR Subchapter J
Emissions	<ul style="list-style-type: none"> EN 55022 Class B⁺ICES-003 Class B⁺ANSI C63.4 2003⁺ETSI EN 300 386 V1.3.3⁺EN 61000-4-2⁺EN 61000-4-3⁺EN 61000-4-4⁺EN 61000-4-5⁺EN 61000-4-6⁺EN 61000-3-2⁺2006⁺EN 61000-3-3⁺1995⁺A1⁺2001⁺A2⁺2005⁺EMC Directive 2004/108/EC⁺EN 55024⁺1998⁺A1⁺2001⁺A2⁺2003⁺EN 61000-4-11⁺2004⁺EN 61000-4-8⁺2001⁺AS/NZS CISPR 22 Class B⁺FCC (CFR 47, Part 15) Class B
Telecom	<ul style="list-style-type: none"> FCC part 68⁺CS-03
Management	<ul style="list-style-type: none"> IMC - Intelligent Management Center⁺command-line interface⁺Web browser⁺out-of-band management (serial RS-232C)⁺out-of-band management (DB-9 serial port console)⁺SNMP Manager⁺Telnet⁺RMON1⁺FTP⁺IEEE 802.3 Ethernet MIB
Notes	<p>The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (802.11b/g, 802.11b/g/n, etc.) in the European Union. Height does not include antennas on wireless models⁺weight is with no optional modules installed. The JF817A is for the Brazilian market only. If other regions have similar requirements, other options are the JF236A, JF809A, JF237A, and JF238A.</p>
Services	<ul style="list-style-type: none"> 3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E) 3-year, 24x7 SW phone support, software updates (UW012E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR555E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR556E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E) 4-year, 24x7 SW phone support, software updates (UW013E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E) 5-year, 24x7 SW phone support, software updates (UW014E) 3 Yr 6 hr Call-to-Repair Onsite (UW079E) 4 Yr 6 hr Call-to-Repair Onsite (UW080E) 5 Yr 6 hr Call-to-Repair Onsite (UW081E) 1-year, 6 hour Call-To-Repair Onsite for hardware (HR558E) 1-year, 24x7 software phone support, software updates (HR557E)

Technical Specifications

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols

(applies to all products in series)

BGP

RFC 1163 Border Gateway Protocol (BGP)
 RFC 1267 Border Gateway Protocol 3 (BGP-3)
 RFC 1657 Definitions of Managed Objects for BGPv4
 RFC 1771 BGPv4
 RFC 1772 Application of the BGP
 RFC 1773 Experience with the BGP-4 Protocol
 RFC 1774 BGP-4 Protocol Analysis
 RFC 1997 BGP Communities Attribute
 RFC 1998 An Application of the BGP Community Attribute in Multi-home Routing
 RFC 2385 BGP Session Protection via TCP MD5
 RFC 2439 BGP Route Flap Damping

Device management

RFC 1305 NTPv3
 RFC 1945 Hypertext Transfer Protocol -- HTTP/1.0
 RFC 2452 MIB for TCP6
 RFC 2454 MIB for UDP6

General protocols

IEEE 802.1D MAC Bridges
 IEEE 802.1p Priority
 IEEE 802.1Q VLANs
 IEEE 802.1s Multiple Spanning Trees
 IEEE 802.1w Rapid Reconfiguration of Spanning Tree
 RFC 768 UDP
 RFC 783 TFTP Protocol (revision 2)
 RFC 791 IP
 RFC 792 ICMP
 RFC 793 TCP
 RFC 826 ARP
 RFC 854 TELNET
 RFC 855 Telnet Option Specification
 RFC 856 TELNET
 RFC 858 Telnet Suppress Go Ahead Option
 RFC 894 IP over Ethernet
 RFC 925 Multi-LAN Address Resolution
 RFC 950 Internet Standard Subnetting Procedure
 RFC 959 File Transfer Protocol (FTP)
 RFC 1006 ISO transport services on top of the TCP
 Version 3

RFC 3279 Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
 RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
 RFC 3392 Support BGP capabilities advertisement
 RFC 3410 Introduction and Applicability Statements for Internet Standard Management Framework
 RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)
 RFC 3564 Requirements for Support of Differentiated Services-aware MPLS Traffic Engineering
 RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec
 RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers
 RFC 3784 ISIS TE support
 RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit
 RFC 3811 Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management
 RFC 3812 Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB)
 RFC 3847 Restart signaling for IS-IS
 RFC 4301 Security Architecture for the Internet Protocol
 RFC 5101 Specification of the IP Flow Information Export (IPFIX) Protocol for the Exchange of IP Traffic Flow Information
 FRF.1.2 PVC User-to-Network Interface (UNI) Implementation Agreement - July 2000
 FRF.11.1 Voice over Frame Relay Implementation Agreement - May 1997 - Annex J added March 1999
 FRF.12 Frame Relay Fragmentation Implementation Agreement - December 1997
 FRF.16.1 Multilink Frame Relay UNI/NNI Implementation Agreement - May 2002
 FRF.2.2 Frame Relay Network-to-Network Interface

Technical Specifications

RFC 1027 Proxy ARP	(NNI) Implementation Agreement - March 2002
RFC 1034 Domain Concepts and Facilities	FRF.20 Frame Relay IP Header Compression
RFC 1035 Domain Implementation and Specification	Implementation Agreement - June 2001
RFC 1042 IP Datagrams	FRF.3.2 Frame Relay Multiprotocol Encapsulation
RFC 1058 RIPv1	Implementation Agreement - April 2000
RFC 1071 Computing the Internet Checksum	FRF.7 Frame Relay PVC Multicast Service and
RFC 1091 Telnet Terminal-Type Option	Protocol Description - October 1994
RFC 1122 Host Requirements	FRF.9 Data Compression Over Frame Relay
RFC 1141 Incremental updating of the Internet	Implementation Agreement - January 1996
checksum	
RFC 1142 OSI IS-IS Intra-domain Routing Protocol	IP multicast
RFC 1144 Compressing TCP/IP headers for low-	RFC 1112 IGMP
speed serial links	RFC 2236 IGMPv2
RFC 1195 OSI ISIS for IP and Dual Environments	RFC 2283 Multiprotocol Extensions for BGP-4
RFC 1256 ICMP Router Discovery Protocol (IRDP)	RFC 2362 PIM Sparse Mode
RFC 1293 Inverse Address Resolution Protocol	RFC 2365 Administratively Scoped IP Multicast
RFC 1315 Management Information Base for Frame	RFC 2710 Multicast Listener Discovery (MLD) for
Relay DTEs	IPv6
RFC 1332 The PPP Internet Protocol Control	RFC 2934 Protocol Independent Multicast MIB for
Protocol (IPCP)	IPv4
RFC 1333 PPP Link Quality Monitoring	RFC 3376 IGMPv3
RFC 1334 PPP Authentication Protocols (PAP)	
RFC 1349 Type of Service	IPv6
RFC 1350 TFTP Protocol (revision 2)	RFC 1981 IPv6 Path MTU Discovery
RFC 1377 The PPP OSI Network Layer Control	RFC 2080 RIPng for IPv6
Protocol (OSINLCP)	RFC 2292 Advanced Sockets API for IPv6
RFC 1381 SNMP MIB Extension for X.25 LAPB	RFC 2373 IPv6 Addressing Architecture
RFC 1471 The Definitions of Managed Objects for the	RFC 2460 IPv6 Specification
Link Control Protocol of the Point-to-Point Protocol	RFC 2463 ICMPv6
RFC 1472 The Definitions of Managed Objects for the	RFC 2464 Transmission of IPv6 over Ethernet
Security Protocols of the Point-to-Point Protocol	Networks
RFC 1490 Multiprotocol Interconnect over Frame	RFC 2472 IP Version 6 over PPP
Relay	RFC 2473 Generic Packet Tunneling in IPv6
RFC 1519 CIDR	RFC 2475 IPv6 DiffServ Architecture
RFC 1534 DHCP/BOOTP Interoperation	RFC 2529 Transmission of IPv6 Packets over IPv4
RFC 1542 Clarifications and Extensions for the	RFC 2545 Use of MP-BGP-4 for IPv6
Bootstrap Protocol	RFC 2553 Basic Socket Interface Extensions for IPv6
RFC 1552 The PPP Internetworking Packet Exchange	RFC 2740 OSPFv3 for IPv6
Control Protocol (IPXCP)	RFC 2893 Transition Mechanisms for IPv6 Hosts
RFC 1577 Classical IP and ARP over ATM	and Routers
RFC 1613 Cisco Systems X.25 over TCP (XOT)	RFC 3056 Connection of IPv6 Domains via IPv4
RFC 1624 Incremental Internet Checksum	Clouds
RFC 1631 NAT	RFC 3513 IPv6 Addressing Architecture
RFC 1638 PPP Bridging Control Protocol (BCP)	RFC 3596 DNS Extension for IPv6
RFC 1661 The Point-to-Point Protocol (PPP)	

Technical Specifications

RFC 1662 PPP in HDLC-like Framing	MIBs
RFC 1695 Definitions of Managed Objects for ATM Management Version 8.0 using SMIPv2	RFC 1213 MIB II
RFC 1701 Generic Routing Encapsulation	RFC 1229 Interface MIB Extensions
RFC 1702 Generic Routing Encapsulation over IPv4 networks	RFC 1286 Bridge MIB
RFC 1721 RIP-2 Analysis	RFC 1493 Bridge MIB
RFC 1722 RIP-2 Applicability	RFC 1573 SNMP MIB II
RFC 1723 RIP v2	RFC 1724 RIPv2 MIB
RFC 1795 Data Link Switching=Switch-to-Switch Protocol AIW DLSw RIG=DLSw Closed Pages, DLSw Standard Version 1	RFC 1757 Remote Network Monitoring MIB
RFC 1812 IPv4 Routing	RFC 1850 OSPFv2 MIB
RFC 1829 The ESP DES-CBC Transform	RFC 2011 SNMPv2 MIB for IP
RFC 1877 PPP Internet Protocol Control Protocol Extensions for Name Server Addresses	RFC 2012 SNMPv2 MIB for TCP
RFC 1878 Variable Length Subnet Table for IPv4	RFC 2013 SNMPv2 MIB for UDP
RFC 1944 Benchmarking Methodology for Network Interconnect Devices	RFC 2233 Interfaces MIB
RFC 1973 PPP in Frame Relay	RFC 2454 IPV6-UDP-MIB
RFC 1974 PPP Stac LZS Compression Protocol	RFC 2465 IPv6 MIB
RFC 1990 The PPP Multilink Protocol (MP)	RFC 2466 ICMPv6 MIB
RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)	RFC 2618 RADIUS Client MIB
RFC 2091 Trigger RIP	RFC 2620 RADIUS Accounting MIB
RFC 2131 DHCP	RFC 2674 802.1p and IEEE 802.1Q Bridge MIB
RFC 2132 DHCP Options and BOOTP Vendor Extensions	RFC 2737 Entity MIB (Version 2)
RFC 2166 APPN Implementer's Workshop Closed Pages Document DLSw v2.0 Enhancements	RFC 2863 The Interfaces Group MIB
RFC 2205 Resource ReSerVation Protocol (RSVP) - Version 1 Functional Specification	RFC 2933 IGMP MIB
RFC 2280 Routing Policy Specification Language (RPSL)	RFC 3813 MPLS LSR MIB
RFC 2284 EAP over LAN	Network management
RFC 2338 VRRP	IEEE 802.1D (STP)
RFC 2364 PPP Over AAL5	RFC 1155 Structure of Management Information
RFC 2374 An Aggregatable Global Unicast Address Format	RFC 1157 SNMPv1
RFC 2451 The ESP CBC-Mode Cipher Algorithms	RFC 1905 SNMPv2 Protocol Operations
RFC 2453 RIPv2	RFC 2272 SNMPv3 Management Protocol
RFC 2510 Internet X.509 Public Key Infrastructure Certificate Management Protocols	RFC 2273 SNMPv3 Applications
RFC 2511 Internet X.509 Certificate Request Message Format	RFC 2274 USM for SNMPv3
	RFC 2275 VACM for SNMPv3
	RFC 2575 SNMPv3 View-based Access Control Model (VACM)
	RFC 3164 BSD syslog Protocol
	OSPF
	RFC 1245 OSPF protocol analysis
	RFC 1246 Experience with OSPF
	RFC 1587 OSPF NSSA
	RFC 1765 OSPF Database Overflow
	RFC 1850 OSPFv2 Management Information Base (MIB), traps
	RFC 2328 OSPFv2

Technical Specifications

RFC 2516 A Method for Transmitting PPP Over Ethernet (PPPoE)	RFC 2370 OSPF Opaque LSA Option
RFC 2570 Introduction to Version 3 of the Internet-standard Network Management Framework	RFC 3101 OSPF NSSA
RFC 2644 Directed Broadcast Control	QoS/CoS
RFC 2661 L2TP	IEEE 802.1P (CoS)
RFC 2663 NAT Terminology and Considerations	RFC 2474 DS Field in the IPv4 and IPv6 Headers
RFC 2684 Multiprotocol Encapsulation over ATM Adaptation Layer 5	RFC 2475 DiffServ Architecture
RFC 2694 DNS extensions to Network Address Translators (DNS, ALG)	RFC 2597 DiffServ Assured Forwarding (AF)
RFC 2702 Requirements for Traffic Engineering Over MPLS	RFC 2598 DiffServ Expedited Forwarding (EF)
RFC 2747 RSVP Cryptographic Authentication	RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP
RFC 2763 Dynamic Name-to-System ID mapping support	Security
RFC 2765 Stateless IP/ICMP Translation Algorithm (SIIT)	IEEE 802.1X Port Based Network Access Control
RFC 2766 Network Address Translation - Protocol Translation (NAT-PT)	RFC 1321 The MD5 Message-Digest Algorithm
RFC 2784 Generic Routing Encapsulation (GRE)	RFC 2082 RIP-2 MD5 Authentication
RFC 2787 Definitions of Managed Objects for VRRP	RFC 2104 Keyed-Hashing for Message Authentication
RFC 2961 RSVP Refresh Overhead Reduction Extensions	RFC 2138 RADIUS Authentication
RFC 2966 Domain-wide Prefix Distribution with Two Level IS-IS	RFC 2209 RSVP-Message Processing
RFC 2973 IS-IS Mesh Groups	RFC 2246 Transport Layer Security (TLS)
RFC 2985 PKCS #9-Selected Object Classes and Attribute Types Version 2.0	RFC 2716 PPP EAP TLS Authentication Protocol
RFC 2993 Architectural Implications of NAT	RFC 2865 RADIUS Authentication
RFC 3022 Traditional IP Network Address Translator (Traditional NAT)	RFC 2866 RADIUS Accounting
RFC 3027 Protocol Complications with the IP Network Address Translator	RFC 3567 Intermediate System (IS) to IS Cryptographic Authentication
RFC 3031 Multiprotocol Label Switching Architecture	VPN
RFC 3032 MPLS Label Stack Encoding	RFC 2403 - HMAC-MD5-96
RFC 3036 LDP Specification	RFC 2404 - HMAC-SHA1-96
RFC 3046 DHCP Relay Agent Information Option	RFC 2405 - DES-CBC Cipher algorithm
RFC 3063 MPLS Loop Prevention Mechanism	RFC 2547 BGP/MPLS VPNs
RFC 3065 Support AS confederation	RFC 2796 BGP Route Reflection - An Alternative to Full Mesh IBGP
RFC 3137 OSPF Stub Router Advertisement	RFC 2842 Capabilities Advertisement with BGP-4
RFC 3209 RSVP-TE Extensions to RSVP for LSP Tunnels	RFC 2858 Multiprotocol Extensions for BGP-4
RFC 3210 Applicability Statement for Extensions to RSVP for LSP-Tunnels	RFC 2918 Route Refresh Capability for BGP-4
	RFC 3107 Carrying Label Information in BGP-4
	IPsec
	RFC 1828 IP Authentication using Keyed MD5
	RFC 2401 IP Security Architecture
	RFC 2402 IP Authentication Header
	RFC 2406 IP Encapsulating Security Payload
	RFC 2407 - Domain of interpretation

Technical Specifications

RFC 3212 Constraint-Based LSP setup using LDP (CR-LDP)

RFC 3214 LSP Modification Using CR-LDP

RFC 3215 LDP State Machine

RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS)

RFC 3277 IS-IS Transient Blackhole Avoidance

RFC 2410 - The NULL Encryption Algorithm and its use with IPsec

RFC 2411 IP Security Document Roadmap

RFC 2412 – OAKLEY

RFC 2865 - Remote Authentication Dial In User Service (RADIUS)

IKEv1

RFC 2865 - Remote Authentication Dial In User Service (RADIUS)

RFC 3748 - Extensible Authentication Protocol (EAP)

Accessories

HP MSR20-1x Series accessories

Transceivers

HP X115 100M SFP LC FX Transceiver	JD102B
HP X110 100M SFP LC LX Transceiver	JD120B
HP X110 100M SFP LC LH40 Transceiver	JD090A
HP X110 100M SFP LC LH80 Transceiver	JD091A
HP X120 1G SFP LC SX Transceiver	JD118B
HP X120 1G SFP LC LX Transceiver	JD119B
HP X125 1G SFP LC LH40 1310nm Transceiver	JD061A
HP X120 1G SFP LC LH40 1550nm Transceiver	JD062A
HP X125 1G SFP LC LH70 Transceiver	JD063B
HP X120 1G SFP LC LH100 Transceiver	JD103A
HP X120 1G SFP LC BX 10-U Transceiver	JD098B
HP X120 1G SFP LC BX 10-D Transceiver	JD099B

Cables

HP X200 V.24 DTE 3m Serial Port Cable	JD519A
HP X200 V.24 DCE 3m Serial Port Cable	JD521A
HP X200 V.35 DTE 3m Serial Port Cable	JD523A
HP X200 V.35 DCE 3m Serial Port Cable	JD525A
HP X200 X.21 DTE 3m Serial Port Cable	JD527A
HP X200 X.21 DCE 3m Serial Port Cable	JD529A
HP X260 RS449 3m DTE Serial Port Cable	JF825A
HP X260 RS449 3m DCE Serial Port Cable	JF826A
HP X260 RS530 3m DTE Serial Port Cable	JF827A
HP X260 RS530 3m DCE Serial Port Cable	JF828A
HP X260 Auxiliary Router Cable	JD508A
HP X260 E1 RJ45 3m Router Cable	JD509A
HP X260 E1 2 BNC 75 ohm 40m Router Cable	JD516A
HP X260 E1 (2) BNC 75 ohm 3m Router Cable	JD175A
HP X260 E1 BNC 20m Router Cable	JD514A
HP X260 E1 RJ45 BNC 75-120 ohm Conversion Router Cable	JD511A
HP X260 2E1 BNC 3m Router Cable	JD643A
HP X260 T1 Voice Router Cable	JD535A
HP X260 T1 Router Cable	JD518A
HP X260 SIC-8AS RJ45 0.28m Router Cable	JD642A
HP X260 E1 RJ45 20m Router Cable	JD517A
HP X260 T1VI DB15M RJ45 3m Router Cable	JF843A
HP X260 mini D-28 to 4-RJ45 0.3m Router Cable	JG263A

Accessories

Mounting Kit

HP 3100/4210-16/-8 PoE Rack Mount Kit JD323A

Router Modules

HP MSR 9-port 10/100 DSIC Module JD574B

HP MSR 4-port 10/100 SIC Module JD573B

HP MSR 1-port 10/100/1000 SIC Module JD572A

HP MSR 1-port 10/100 SIC Module JD545B

HP 1-port 100Mbt SFP SIC Router Module JF280A

HP MSR 2-port FXO SIC Module JD558A

HP MSR 1-port FXO SIC Module JD559A

HP MSR 2-port FXS SIC Module JD560A

HP MSR 1-port FXS SIC Module JD561A

HP MSR 2 FXS +1 FXO Voice Interface SIC Module JD632A

HP 2-port ISDN-S/T Voice Interface SIC Module JF821A

HP MSR 1-port ADSL2+ SIC Module JD537A

[HP MSR 1-port ADSL over ISDN BRI U SIC Module](#) JG056B

HP MSR 1-port 8-wire G.SHDSL (RJ45) DSIC Module JG191A

HP MSR 1-port Fractional E1 SIC Module JD634B

HP MSR 2-port Fractional E1 SIC Module JF842A

HP MSR 1-port Fractional SIC Module JD538A

HP MSR 1-port Enhanced Serial SIC Module JD557A

HP MSR 1-port ISDN-S/T SIC Module JD571A

HP MSR 16-port Async Serial SIC Module JG186A

[HP 8-port Asynchronous Serial Interface SIC Router Module](#) JF281A

HP 802.11b/g/n Wireless AP SIC Module JF819A

HP MSR 802.11b/g/n Wireless Access Point SIC Module (NA) JG211A

HP MSR 1-port E1/CE1/PRI SIC Module JF253B

HP MSR 4-port FXS / 1-port FXO DSIC Module JG189A

HP MSR HSPA/WCDMA SIC Module JG187A

HP MSR20-12 Router (JF241A)

HP MSR 1-port E1-Voice SIC Module JD575A

HP MSR 1-port T1-Voice SIC Module JD576A

HP MSR 32-channel Voice Processor Module JD598A

HP MSR 24-channel Voice Processor Module JD599A

HP MSR 16-channel Voice Processor Module JD600A

HP MSR 8-channel Voice Processor Module JD601A

HP MSR Voice Co-processor Module JD610A

Accessories

HP MSR20-12-W Router (JF807A)

HP MSR 1-port E1-Voice SIC Module	JD575A
HP MSR 1-port T1-Voice SIC Module	JD576A
HP MSR 32-channel Voice Processor Module	JD598A
HP MSR 24-channel Voice Processor Module	JD599A
HP MSR 16-channel Voice Processor Module	JD600A
HP MSR 8-channel Voice Processor Module	JD601A
HP MSR Voice Co-processor Module	JD610A

HP MSR20-12-T Router (JF806A)

HP MSR 1-port E1-Voice SIC Module	JD575A
HP MSR 1-port T1-Voice SIC Module	JD576A
HP MSR 32-channel Voice Processor Module	JD598A
HP MSR 24-channel Voice Processor Module	JD599A
HP MSR 16-channel Voice Processor Module	JD600A
HP MSR 8-channel Voice Processor Module	JD601A
HP MSR Voice Co-processor Module	JD610A

HP MSR20-12-T-W Router (NA) (JG209A)

HP MSR 1-port E1-Voice SIC Module	JD575A
HP MSR 1-port T1-Voice SIC Module	JD576A
HP MSR 32-channel Voice Processor Module	JD598A
HP MSR 24-channel Voice Processor Module	JD599A
HP MSR 16-channel Voice Processor Module	JD600A
HP MSR 8-channel Voice Processor Module	JD601A
HP MSR Voice Co-processor Module	JD610A

HP MSR20-15-A Router (JF237A)

HP MSR 1-port E1-Voice SIC Module	JD575A
HP MSR 1-port T1-Voice SIC Module	JD576A
HP MSR 32-channel Voice Processor Module	JD598A
HP MSR 24-channel Voice Processor Module	JD599A
HP MSR 16-channel Voice Processor Module	JD600A
HP MSR 8-channel Voice Processor Module	JD601A
HP MSR Voice Co-processor Module	JD610A

HP MSR20-15-A-W Router (JF809A)

HP MSR 1-port E1-Voice SIC Module	JD575A
HP MSR 1-port T1-Voice SIC Module	JD576A
HP MSR 32-channel Voice Processor Module	JD598A
HP MSR 24-channel Voice Processor Module	JD599A

Accessories

HP MSR 16-channel Voice Processor Module	JD600A
HP MSR 8-channel Voice Processor Module	JD601A
HP MSR Voice Co-processor Module	JD610A
HP MSR20-15-I Router (JF236A)	
HP MSR 1-port E1-Voice SIC Module	JD575A
HP MSR 1-port T1-Voice SIC Module	JD576A
HP MSR 32-channel Voice Processor Module	JD598A
HP MSR 24-channel Voice Processor Module	JD599A
HP MSR 16-channel Voice Processor Module	JD600A
HP MSR 8-channel Voice Processor Module	JD601A
HP MSR Voice Co-processor Module	JD610A
HP MSR20-15-I-W Router (JF238A)	
HP MSR 1-port E1-Voice SIC Module	JD575A
HP MSR 1-port T1-Voice SIC Module	JD576A
HP MSR 32-channel Voice Processor Module	JD598A
HP MSR 24-channel Voice Processor Module	JD599A
HP MSR 16-channel Voice Processor Module	JD600A
HP MSR 8-channel Voice Processor Module	JD601A
HP MSR Voice Co-processor Module	JD610A
HP MSR20-15 Router (JF817A)	
HP MSR 1-port E1-Voice SIC Module	JD575A
HP MSR 1-port T1-Voice SIC Module	JD576A
HP MSR 32-channel Voice Processor Module	JD598A
HP MSR 24-channel Voice Processor Module	JD599A
HP MSR 16-channel Voice Processor Module	JD600A
HP MSR 8-channel Voice Processor Module	JD601A
HP MSR Voice Co-processor Module	JD610A

Accessory Product Details

NOTE—Details are not available for all accessories. The following specifications were available at the time of publication.

<p>HP X120 1G SFP LC SX Transceiver (JD118B)</p> <p>A small form-factor pluggable (SFP) Gigabit SX transceiver that provides a full-duplex Gigabit solution up to 550m on a Multimode fiber.</p>	Ports	1 LC 1000BASE-SX port	
	Connectivity	Connector type LC	
	Physical characteristics	Wavelength	850 nm
		Dimensions	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
		Full configuration weight	0.04 lb. (0.02 kg)
	Electrical characteristics	Power consumption typical	0.8 W
		Power consumption maximum	1.0 W
	Cabling	Maximum distance [±]	
		<ul style="list-style-type: none"> • FDDI Grade distance = 220m • OM1 = 275m • OM2 = 500m • OM3 = Not Specified by standard 	
		Cable length	up to 550m
Services	Fiber type	Multi Mode	
	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.		

<p>HP X120 1G SFP LC LX Transceiver (JD119B)</p> <p>A small form-factor pluggable (SFP) Gigabit LX transceiver that provides a full duplex Gigabit solution up to 550m on MMF or 10Km on SMF</p>	Ports	1 SFP 1000BASE-LX port (IEEE 802.3z Type 1000BASE-LX)	
	Connectivity	Connector type LC	
	Physical characteristics	Wavelength	1300 nm
		Dimensions	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
		Full configuration weight	0.04 lb. (0.02 kg)
	Electrical characteristics	Power consumption typical	0.8 W
		Power consumption maximum	1.0 W
	Cabling	Cable type [±]	
		Either single mode or multimode [±]	
		Maximum distance [±]	
	<ul style="list-style-type: none"> • 550m for Multimode • 10km for Singlemode 		
	Fiber type	Both	

Accessory Product Details

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP X125 1G SFP LC LH40 1310nm Transceiver (JD061A)

A small form-factor pluggable SFP Gigabit LH40 transceiver that provides a full duplex Gigabit solution up to 40km on a single-mode fiber.

Ports

1 LC 1000Base-LH port (no IEEE standard exists for 1550 nm optics)

Connectivity

Connector type LC

Wavelength 1310 nm

Physical characteristics

Dimensions 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)

Full configuration weight 0.04 lb. (0.02 kg)

Electrical characteristics

Power consumption typical 0.8 W

Power consumption maximum 1.0 W

Cabling

Cable type²

Single-mode fiber optic, complying with ITU-T G.652⁷

Maximum distance²

- 40km distance

Fiber type Single Mode

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP X120 1G SFP LC LH40 1550nm Transceiver (JD062A)

A small form-factor pluggable (SFP) Gigabit LH40 transceiver that provides a full-duplex Gigabit solution up to 40 km on a single mode fiber.

Ports

1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics)

Connectivity

Connector type LC

Wavelength 1550 nm

Physical characteristics

Dimensions 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)

Full configuration weight 0.04 lb. (0.02 kg)

Electrical characteristics

Power consumption typical 0.8 W

Power consumption maximum 1.0 W

Cabling

Cable type²

Single-mode fiber optic, complying with ITU-T G.652⁷

Maximum distance²

- 40km distance

Fiber type Single Mode

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP X125 1G SFP LC LH70 Transceiver (JD063B)

A small form-factor pluggable (SFP) Gigabit LH70 transceiver that provides a full-duplex Gigabit solution up to 70km on a single-mode fiber.

Ports	1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics)
Connectivity	Connector type LC
Physical characteristics	Wavelength 1550 nm
Electrical characteristics	Dimensions 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
Cabling	Full configuration weight 0.04 lb. (0.02 kg)
Services	Power consumption typical 0.8 W
	Power consumption maximum 1.0 W
	Cable type Single-mode fiber optic, complying with ITU-T G.652 [†]
	Maximum distance 70km
	Fiber type Single Mode
	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP X120 1G SFP LC BX10-U Transceiver (JD098B)

A small form-factor pluggable (SFP) Gigabit LX-BX10-U transceiver that provides a full duplex Gigabit solution up to 10km on a single mode cable.

Ports	1 LC 1000BASE-BX10 port (IEEE 802.3ah Type 1000BASE-BX10-U) [†] Duplex [†] full only
Connectivity	Connector type LC
Physical characteristics	Dimensions 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
Electrical characteristics	Full configuration weight 0.04 lb. (0.02 kg)
Cabling	Power consumption typical 0.8 W
Notes	Power consumption maximum 1.0 W
Services	Maximum distance 10km
	Fiber type Single Mode
	TX 1310nm RX 1490nm
	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

<p>HP X120 1G SFP LC BX10-D Transceiver (JD099B)</p> <p>A small form-factor pluggable (SFP) Gigabit LX-BX10-D transceiver that provides a full duplex Gigabit solution up to 10km on a single mode cable.</p>	Ports	1 LC 1000BASE-BX10 port (IEEE 802.3ah Type 1000BASE-BX10-D)±Duplex± full only		
	Connectivity	Connector type	LC	
	Physical characteristics	Dimensions	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)	
		Full configuration weight	0.04 lb. (0.02 kg)	
	Electrical characteristics	Power consumption typical	0.8 W	
		Power consumption maximum	1.0 W	
	Cabling	Maximum distance±		
		• Up to 10km		
		Fiber type	Single Mode	
	Notes	TX 1490nm RX 1310nm		
Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.			

<p>HP MSR 1-port ADSL over ISDN SIC Module (JG056B)</p>	Notes	This module only provide ISDN U interface	
	Services	Refer to the HP website at± www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

<p>HP MSR 8-port Async Serial SIC Module (JF281A)</p>	Connectivity	Bit rate	115.2Kbps
		Interface	RS232
	Services	Refer to the HP website at± www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

To learn more, visit±www.hp.com/networking

© Copyright 2015 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.