

Overview

Models

HP MSR900 Router	JF812A
HP MSR920 Router	JF813A
HP MSR900-W Router	JF814A
HP MSR920-W Router	JF815A
HP MSR900-W Router (NA)	JG207A
HP MSR920-W Router (NA)	JG208A

Key features

- Converged routing, switching, security, and WLAN
- Integrated 2 Fast Ethernet WAN, 4/8 LAN on board
- Unified 802.11b/g wireless LAN and 3G wireless WAN
- Embedded encryption, firewall, security features
- A unified management platform

Product overview

The HP MSR900 router series is a component of the HP FlexBranch module of the HP FlexNetwork architecture. HP MSR900 series routers deliver integrated routing, switching, security, and 802.11b/g wireless LAN in a single box for secure, reliable small branch connectivity. These routers are perfect %branch-in-a-box% appliances that deliver converged network solutions, including data, voice and video, IPv6 support, and robust Quality of Service (QoS), and help ensure that they can handle both current enterprise networking applications as well as the future connectivity and capacity demands of an HP FlexNetwork architecture. Additionally, a standards-based design provides complete interoperability in multivendor environments.

Features and benefits

Quality of Service (QoS)

- **Traffic policing**—supports Committed Access Rate (CAR) and line rate
- **Congestion management**—supports FIFO, PQ, CQ, WFQ, CBQ, and RTPQ
- **Congestion avoidance**—Weighted Random Early Detection (WRED)/Random Early Detection (RED)
- **Other QoS technologies**—support traffic shaping, FR QoS, and MP QoS/LFI

Management

- **Industry-standard CLI with a hierarchical structure**—reduces training time and expenses, and increases productivity in multivendor installations
- **Management security**—multiple privilege levels, with password protection, restrict access to critical configuration commands—ACLs provide telnet and SNMP access—local and remote syslog capabilities allow logging of all access
- **SNMPv1, v2, and v3**—provide complete support of SNMP—provide full support of industry-standard Management Information Base (MIB) plus private extensions—SNMPv3 supports increased security using encryption
- **Remote monitoring (RMON)**—uses standard SNMP to monitor essential network functions—supports events, alarm, history, and

Overview

- statistics group plus a private alarm extension group
- **FTP, TFTP, and SFTP support**—FTP allows bidirectional transfers over a TCP/IP network and is used for configuration updates—Trivial FTP is a simpler method using User Datagram Protocol (UDP)
- **Debug and sampler utility**—supports ping and traceroute for both IPv4 and IPv6
- **Network Time Protocol (NTP)**—synchronizes timekeeping among distributed time servers and clients—keeps consistent timekeeping among all clock-dependent devices within the network so that the devices can provide diverse applications based on the consistent time
- **Info center**—provides a central information center for system and network information—aggregates all logs, traps, and debugging information generated by the system and maintains them in order of severity—outputs the network information to multiple channels based on user-defined rules
- **Network Quality Analyzer (NQA)**—analyzes network performance and service quality by sending test packets, and provides network performance and service quality parameters such as jitter, TCP, or FTP connection delays—allows network manager to determine overall network performance and diagnose and locate network congestion points or failures

Connectivity

- **Packet storm protection**—protects against broadcast, multicast, or unicast storms with user-defined thresholds
- **Loopback**—supports internal loopback testing for maintenance purposes and an increase in availability—loopback detection protects against incorrect cabling or network configurations and can be enabled on a per-port or per-VLAN basis for added flexibility
- **3G access support**—provides support for popular USB 3G modems—for a list of specific modems, please refer to your local product manager

Performance

- **Excellent forwarding performance**—provides forwarding performance up to 100 Kpps—meets current and future bandwidth-intensive application demands for enterprise businesses
- **Embedded encryption**—supports up to 100 VPN tunnels and 8 Mbps encryption throughput

Resiliency and high availability

- **Backup Center**—acts as a part of the management and backup function to provide backup for device interfaces—delivers reliability by switching traffic over to a backup interface when the primary one fails
- **Virtual Router Redundancy Protocol (VRRP)**: allows groups of two routers to dynamically back each other up to create highly available routed environments—supports VRRP load balancing

Layer 2 switching

- **Spanning Tree Protocol**—fully supports standard IEEE 802.1D Spanning Tree Protocol, IEEE 802.1w Rapid Spanning Tree Protocol for faster convergence, and IEEE 802.1s Multiple Spanning Tree Protocol
- **Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) protocol snooping**—effectively control and manage the flooding of multicast packets in a Layer 2 network
- **Port mirroring**—duplicates port traffic (ingress and egress) to a local or remote monitoring port
- **Port isolation**—increases security by isolating ports within a VLAN while still allowing them to communicate with other VLANs
- **VLANs**—support IEEE 802.1Q-based VLANs
- **sFlow**—allows traffic sampling

Layer 3 services

-



Overview

- **Address Resolution Protocol (ARP)**—determines the MAC address of another IP host in the same subnet—supports static ARPs—gratuitous ARP allows detection of duplicate IP addresses—proxy ARP allows normal ARP operation between subnets or when subnets are separated by a Layer 2 network
- **Dynamic Host Configuration Protocol (DHCP)**—simplifies the management of large IP networks and supports client and server—DHCP Relay enables DHCP operation across subnets

Layer 3 routing

- **Static IPv4 routing**—provides simple, manually configured IPv4 routing
- **Routing Information Protocol**—uses a distance vector algorithm with UDP packets for route determination—supports RIPv1 and RIPv2 routing—includes loop protection
- **OSPF**—Interior Gateway Protocol (IGP) uses link-state protocol for faster convergence—supports ECMP, NSSA, and MD5 authentication for increased security and graceful restart for faster failure recovery
- **Border Gateway Protocol 4 (BGP-4)**—Exterior Gateway Protocol (EGP) with path vector protocol uses TCP for enhanced reliability for the route discovery process, reduces bandwidth consumption by advertising only incremental updates, and supports extensive policies for increased flexibility, as well as scales to very large networks
- **Intermediate system to intermediate system (IS-IS)**—Interior Gateway Protocol (IGP) using path vector protocol, which is defined by the ISO organization for IS-IS routing and extended by IETF RFC 1195 to operate in both TCP/IP and the OSI reference model (Integrated IS-IS)
- **Static IPv6 routing**—provides simple, manually configured IPv6 routing
- **Dual IP stack**—maintains separate stacks for IPv4 and IPv6 to ease transition from an IPv4-only network to an IPv6-only network design
- **Routing Information Protocol next generation (RIPng)**—extends RIPv2 to support IPv6 addressing
- **OSPFv3**—provides OSPF support for IPv6
- **BGP+**—extends BGP-4 to support Multiprotocol BGP (MBGP), including support for IPv6 addressing
- **IS-IS for IPv6**—extends IS-IS to support IPv6 addressing
- **IPv6 tunneling**—is an important element for the transition from IPv4 to IPv6—allows IPv6 packets to traverse IPv4-only networks by encapsulating the IPv6 packet into a standard IPv4 packet—supports manually configured, 6to4, and Intra-Site Automatic Tunnel Addressing Protocol (ISATAP) tunnels
- **Policy routing**—allows custom filters for increased performance and security—supports ACLs, IP prefix, AS paths, community lists, and aggregate policies

Security

- **Access control list (ACL)**—supports powerful ACLs for both IPv4 and IPv6—ACLs are used for filtering traffic to prevent unauthorized users from accessing the network, or for controlling network traffic to save resources—rules can either deny or permit traffic to be forwarded—rules can be based on a Layer 2 header or a Layer 3 protocol header—rules can be set to operate on specific dates or times
- **TACACS+**—is an authentication tool using TCP with encryption of the full authentication request that provides added security
- **Network login**—standard IEEE 802.1x allows authentication of multiple users per port
- **RADIUS**—eases security access administration by using a password authentication server
- **Network address translation (NAT)**—supports one-to-one NAT, many-to-many NAT, and NAT control, enabling NAT-PT to support multiple connections—supports backlog in NAT/NAT-PT, a limit on the number of connections, session logs, and multi-instances
- **Secure Shell (SSHv2)**—uses external servers to securely login into a remote device or securely login into MSR from a remote location—with authentication and encryption, it protects against IP spoofing and plain text password interception—increases the security of SFTP transfers

Overview

- **Unicast Reverse Path Forwarding (URPF)**—allows normal packets to be forwarded correctly, but discards the attaching packet due to lack of reverse path route or incorrect inbound interface—prevents source spoofing and distributed attacks
- **IPSec VPN**—supports DES, 3DES, and AES 128/192/256 encryption, and MD5 and SHA-1 authentication
- **Dynamic Virtual Private Network (DVPN)**—collects, maintains, and distributes dynamic public addresses through the VPN Address Management (VAM) protocol, making VPN establishment available between enterprise branches that use dynamic addresses to access the public network—compared to traditional VPN technologies, DVPN technology is more flexible and has richer features, such as NAT traversal of DVPN packets, AAA identity authentication, IPSec protection of data packets, and multiple VPN domains

Convergence

- **Internet Group Management Protocol (IGMP)**—is used by IP hosts to establish and maintain multicast groups—supports IGMPv1, v2, and v3—utilizes Any-Source Multicast (ASM) or Source-Specific Multicast (SSM) to manage IPv4 multicast networks
- **Protocol Independent Multicast (PIM)**—is used for IPv4 and IPv6 multicast applications—supports PIM Dense Mode (PIM-DM), Sparse Mode (PIM-SM), and Source-Specific Mode (PIM-SSM)
- **Multicast Source Discovery Protocol (MSDP)**—is used for inter-domain multicast applications, allowing multiple PIM-SM domains to interoperate
- **Multicast Border Gateway Protocol (MBGP)**—allows multicast traffic to be forwarded across BGP networks and kept separate from unicast traffic

Integration

- **Embedded NetStream**—local and global server load-balancing module improves traffic distribution using powerful scheduling algorithms, including Layer 4 to 7 services—monitors the health status of servers and firewalls
- **Embedded VPN firewall**—provides enhanced stateful packet inspection and filtering—provides advanced VPN services with Triple DES (3DES) and Advanced Encryption Standard (AES) encryption at high performance and low latency, Web content filtering, and application prioritization and enhancement

Additional information

- **Green initiative support**—provides support for RoHS and WEEE regulations
- **OPEX savings**—a common operating system simplifies and streamlines deployment, management, and training, thereby cutting costs as well as reducing the chance for human errors associated with having to manage multiple operating systems across different platforms and network layers
- **Faster time to market**—engineering efficiencies allow new and custom features to be brought rapidly to the market with better initial and ongoing stability

Warranty and support

- **1-year warranty**—with advance replacement and delivery (available in most countries)
- **Electronic and telephone support**—limited electronic and telephone support is available from HP—to reach our support centers, refer to—www.hp.com/networking/contact-support—for details on the duration of support provided with your product purchase, refer to www.hp.com/networking/warrantysummary
- **Software releases**—to find software for your product, refer to—www.hp.com/networking/support—for details on the software releases available with your product purchase, refer to—www.hp.com/networking/warrantysummary

Technical Specifications

HP MSR900 Router (JF812A)

Ports	2 RJ-45 autosensing 10/100 WAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX)† Duplex=half or full
	4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX)† Duplex=half or full
Physical characteristics	Dimensions 6.3(d) x 9.06(w) x 1.74(h) in. (16 x 23 x 4.42 cm)
	Weight 3.97 lb. (1.8 kg)
Memory and processor	Processor RISC @ 266 MHz, 256 MB DDR SDRAM, 256 MB flash
Performance	Throughput up to 70 Kpps (64-byte packets)
	Routing table size 10000 entries
Environment	Operating temperature 32°F to 113°F (0°C to 45°C)
	Operating relative humidity 5% to 90%
	Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity 5% to 90%
Electrical characteristics	Maximum heat dissipation 20 BTU/hr (21.1 kJ/hr)
	DC Voltage 12 V
	Maximum power rating 15 W
	Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1†CAN/CSA 22.2 No. 60950-1†AS/NZS 60950†EN 60825-1 Safety of Laser Products-Part 1†EN 60825-2 Safety of Laser Products-Part 2†IEC 60950-1†CAN/CSA-C22.2 No. 60950-1-03†EN 60950-1/A11†FDA 21 CFR Subchapter J
Emissions	ANSI C63.4†EN 55022 Class B†ICES-003 Class B†ETSI EN 300 386 V1.3.3†EN 61000-4-2†EN 61000-4-3†EN 61000-4-4†EN 61000-4-5†EN 61000-4-6†EN 61000-3-2†2006†EN 61000-3-3†1995 +A1†2001+A2†2005†EMC Directive 2004/108/EC†EN 55024†1998+ A1†2001 + A2†2003†EN 61000-4-11†2004†EN 61000-4-8†2001†AS/NZS CISPR22 Class B†FCC (CFR 47, Part 15) Class B
Telecom	FCC part 68
Management	IMC - Intelligent Management Center†command-line interface†Web browser†SNMP Manager†Telnet†RMON1†FTP†IEEE 802.3 Ethernet MIB
Services	3-year, parts only, global next-day advance exchange (UY865E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UY866E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UY869E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UY872E) 3-year, 24x7 SW phone support, software updates (UY875E)

Technical Specifications

- 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR648E)
- 4-year, 4-hour onsite, 13x5 coverage for hardware (UY867E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware (UY870E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UY873E)
- 4-year, 24x7 SW phone support, software updates (UY876E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UY868E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UY871E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UY874E)
- 5-year, 24x7 SW phone support, software updates (UY877E)
- 3 Yr 6 hr Call-to-Repair Onsite (UY878E)
- 4 Yr 6 hr Call-to-Repair Onsite (UY879E)
- 5 Yr 6 hr Call-to-Repair Onsite (UY880E)
- 1-year, 4-hour onsite, 24x7 coverage for hardware (HR649E)
- 1-year, 6 hour Call-To-Repair Onsite for hardware (HR652E)
- 1-year, 24x7 software phone support, software updates (HR651E)
- 1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR650E)

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP MSR920 Router (JF813A)

Ports	2 RJ-45 autosensing 10/100 WAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX) [†] Duplex=half or full	
	8 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX) [†] Duplex=half or full	
Physical characteristics	Dimensions	6.3(d) x 9.06(w) x 1.74(h) in. (16 x 23 x 4.42 cm)
	Weight	3.97 lb. (1.8 kg)
Memory and processor	Processor	RISC @ 333 MHz, 256 MB DDR SDRAM, 256 MB flash
Performance	Throughput	up to 100 Kpps (64-byte packets)
	Routing table size	10000 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C)
	Operating relative humidity	5% to 90%
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 90%
Electrical characteristics	Maximum heat dissipation	29 BTU/hr (30.6 kJ/hr)
	DC Voltage	12 V



Technical Specifications

Maximum power rating 15 W

Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.

Safety UL 60950-1 CAN/CSA 22.2 No. 60950-1 AS/NZS 60950 EN 60825-1 Safety of Laser Products-Part 1 EN 60825-2 Safety of Laser Products-Part 2 IEC 60950-1 CAN/CSA-C22.2 No. 60950-1-03 EN 60950-1/A117 FDA 21 CFR Subchapter J

Emissions ANSI C63.4 EN 55022 Class B ICES-003 Class B ETSI EN 300 386 V1.3.3 EN 61000-4-2 EN 61000-4-3 EN 61000-4-4 EN 61000-4-5 EN 61000-4-6 EN 61000-3-2 2006 EN 61000-3-3 1995 +A1 2001 +A2 2005 EMC Directive 2004/108/EC EN 55024 1998 + A1 2001 + A2 2003 EN 61000-4-11 2004 EN 61000-4-8 2001 AS/NZS CISPR22 Class B FCC (CFR 47, Part 15) Class B

Telecom FCC part 68

Management IMC - Intelligent Management Center command-line interface Web browser SNMP Manager Telnet RMON1 FTP IEEE 802.3 Ethernet MIB

Services

- 3-year, parts only, global next-day advance exchange (UY881E)
- 3-year, 4-hour onsite, 13x5 coverage for hardware (UY882E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware (UY885E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UY888E)
- 3-year, 24x7 SW phone support, software updates (UY891E)
- 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR653E)
- 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR654E)
- 4-year, 4-hour onsite, 13x5 coverage for hardware (UY883E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware (UY886E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UY889E)
- 4-year, 24x7 SW phone support, software updates (UY892E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UY884E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UY887E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UY890E)
- 5-year, 24x7 SW phone support, software updates (UY893E)
- 3 Yr 6 hr Call-to-Repair Onsite (UY894E)
- 4 Yr 6 hr Call-to-Repair Onsite (UY895E)
- 5 Yr 6 hr Call-to-Repair Onsite (UY896E)
- 1-year, 6 hour Call-To-Repair Onsite for hardware (HR657E)
- 1-year, 24x7 software phone support, software updates (HR656E)
- 1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR655E)

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP MSR900-W Router (JF814A)



Technical Specifications

Ports	2 RJ-45 autosensing 10/100 WAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX) [†] Duplex [†] half or full	
	4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX) [†] Duplex [†] half or full	
AP characteristics	Radios	Single (b/g)
	Radio operation modes	Client access
	AP operation modes	Autonomous
	Wi-Fi Alliance Certification*	b/g Wi-Fi Certified
	* HP access points and access devices are Wi-Fi Certified, providing our customers with the assurance that these products have met and passed the rigorous interoperability testing performed by the Wi-Fi Alliance Organization. See the Specifications section of this series for more information.	
Physical characteristics	Dimensions	6.3(d) x 9.06(w) x 1.74(h) in. (16 x 23 x 4.42 cm)
	Weight	3.97 lb. (1.8 kg)
Memory and processor	Processor	RISC @ 266 MHz, 256 MB DDR SDRAM, 256 MB flash
Performance	Throughput	up to 70 Kpps (64-byte packets)
	Routing table size	10000 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C)
	Operating relative humidity	5% to 90%
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 90%
Electrical characteristics	Maximum heat dissipation	20 BTU/hr (21.1 kJ/hr)
	DC Voltage	12 V
	Maximum power rating	15 W
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1 [†] CAN/CSA 22.2 No. 60950-1 [†] AS/NZS 60950 [†] EN 60825-1 Safety of Laser Products-Part 1 [†] EN 60825-2 Safety of Laser Products-Part 2 [†] IEC 60950-1 [†] CAN/CSA-C22.2 No. 60950-1-03 [†] EN 60950-1/A11 [†] FDA 21 CFR Subchapter J	
Emissions	ANSI C63.4 [†] EN 55022 Class B [†] ICES-003 Class B [†] ETSI EN 300 386 V1.3.3 [†] EN 61000-4-2 [†] EN 61000-4-3 [†] EN 61000-4-4 [†] EN 61000-4-5 [†] EN 61000-4-6 [†] EN 61000-3-2 [†] 2006 [†] EN 61000-3-3 [†] 1995 +A1 [†] 2001+A2 [†] 2005 [†] EMC Directive 2004/108/EC [†] EN 55024 [†] 1998+ A1 [†] 2001 + A2 [†] 2003 [†] EN 61000-4-11 [†] 2004 [†] EN 61000-4-8 [†] 2001 [†] AS/NZS CISPR22 Class B [†] FCC (CFR 47, Part 15) Class B	
Telecom	FCC part 68	

Technical Specifications

Management	IMC - Intelligent Management Center [†] command-line interface [†] Web browser [†] SNMP Manager [†] Telnet [†] RMON1 [†] FTP [†] IEEE 802.3 Ethernet MIB
Services	<p>3-year, parts only, global next-day advance exchange (UY865E)</p> <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UY866E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UY869E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UY872E)</p> <p>3-year, 24x7 SW phone support, software updates (UY875E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR648E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UY867E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UY870E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UY873E)</p> <p>4-year, 24x7 SW phone support, software updates (UY876E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UY868E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UY871E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UY874E)</p> <p>5-year, 24x7 SW phone support, software updates (UY877E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UY878E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UY879E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UY880E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware (HR649E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR652E)</p> <p>1-year, 24x7 software phone support, software updates (HR651E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR650E)</p>

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP MSR920-W Router (JF815A)

Ports	2 RJ-45 autosensing 10/100 WAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX) [†] Duplex [†] half or full	
	8 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX) [†] Duplex [†] half or full	
AP characteristics	Radios	Single (b/g)
	Radio operation modes	Client access
	AP operation modes	Autonomous
	Wi-Fi Alliance Certification*	b/g Wi-Fi Certified

* HP access points and access devices are Wi-Fi Certified, providing our customers with the assurance that these products have met and passed the rigorous interoperability testing performed by the Wi-Fi Alliance Organization. See the Specifications section of this series for more information.

Technical Specifications

Physical characteristics	Dimensions	6.3(d) x 9.06(w) x 1.74(h) in. (16 x 23 x 4.42 cm)
	Weight	3.97 lb. (1.8 kg)
Memory and processor	Processor	RISC @ 333 MHz, 256 MB DDR SDRAM, 256 MB flash
	Performance	
	Throughput	up to 100 Kpps (64-byte packets)
	Routing table size	10000 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C)
	Operating relative humidity	5% to 90%
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 90%
Electrical characteristics	Maximum heat dissipation	29 BTU/hr (30.6 kJ/hr)
	DC Voltage	12 V
	Maximum power rating	15 W
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1 CAN/CSA 22.2 No. 60950-1 AS/NZS 60950 EN 60825-1 Safety of Laser Products-Part 1 EN 60825-2 Safety of Laser Products-Part 2 IEC 60950-1 CAN/CSA-C22.2 No. 60950-1-03 EN 60950-1/A11 FDA 21 CFR Subchapter J	
Emissions	ANSI C63.4 EN 55022 Class B ICES-003 Class B ETSI EN 300 386 V1.3.3 EN 61000-4-2 EN 61000-4-3 EN 61000-4-4 EN 61000-4-5 EN 61000-4-6 EN 61000-3-2 2006 EN 61000-3-3 1995 +A1 2001 +A2 2005 EMC Directive 2004/108/EC EN 55024 1998 + A1 2001 + A2 2003 EN 61000-4-11 2004 EN 61000-4-8 2001 AS/NZS CISPR22 Class B FCC (CFR 47, Part 15) Class B	
Telecom	FCC part 68	
Management	IMC - Intelligent Management Center command-line interface Web browser SNMP Manager Telnet RMON1 FTP IEEE 802.3 Ethernet MIB	
Services	3-year, parts only, global next-day advance exchange (UY881E)	
	3-year, 4-hour onsite, 13x5 coverage for hardware (UY882E)	
	3-year, 4-hour onsite, 24x7 coverage for hardware (UY885E)	
	3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UY888E)	
	3-year, 24x7 SW phone support, software updates (UY891E)	
	1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR653E)	
	1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR654E)	
	4-year, 4-hour onsite, 13x5 coverage for hardware (UY883E)	
4-year, 4-hour onsite, 24x7 coverage for hardware (UY886E)		
4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UY889E)		
4-year, 24x7 SW phone support, software updates (UY892E)		

Technical Specifications

- 5-year, 4-hour onsite, 13x5 coverage for hardware (UY884E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UY887E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UY890E)
- 5-year, 24x7 SW phone support, software updates (UY893E)
- 3 Yr 6 hr Call-to-Repair Onsite (UY894E)
- 4 Yr 6 hr Call-to-Repair Onsite (UY895E)
- 5 Yr 6 hr Call-to-Repair Onsite (UY896E)
- 1-year, 6 hour Call-To-Repair Onsite for hardware (HR657E)
- 1-year, 24x7 software phone support, software updates (HR656E)
- 1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR655E)

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP MSR900-W Router (NA) (JG207A)

Ports	2 RJ-45 autosensing 10/100 WAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX)† Duplex=half or full	
	4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX)† Duplex=half or full	
AP characteristics	Radios	Single (b/g)
	Radio operation modes	Client access
	AP operation modes	Autonomous
	Wi-Fi Alliance Certification*	b/g Wi-Fi Certified
	* HP access points and access devices are Wi-Fi Certified, providing our customers with the assurance that these products have met and passed the rigorous interoperability testing performed by the Wi-Fi Alliance Organization. See the Specifications section of this series for more information.	
Physical characteristics	Dimensions	6.3(d) x 9.06(w) x 1.74(h) in. (16 x 23 x 4.42 cm)
	Weight	3.97 lb. (1.8 kg)
Memory and processor	Processor	RISC @ 266 MHz, 256 MB DDR SDRAM, 256 MB flash
Performance	Throughput	up to 70 Kpps (64-byte packets)
	Routing table size	10000 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C)
	Operating relative humidity	5% to 90%
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 90%

Technical Specifications

Electrical characteristics	Maximum heat dissipation	20 BTU/hr (21.1 kJ/hr)
	DC Voltage	12 V
	Maximum power rating	15 W
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1 CAN/CSA 22.2 No. 60950-1 AS/NZS 60950 EN 60825-1 Safety of Laser Products-Part 1 EN 60825-2 Safety of Laser Products-Part 2 IEC 60950-1 CAN/CSA-C22.2 No. 60950-1-03 EN 60950-1/A11 FDA 21 CFR Subchapter J	
Emissions	ANSI C63.4 EN 55022 Class B ICES-003 Class B ETSI EN 300 386 V1.3.3 EN 61000-4-2 EN 61000-4-3 EN 61000-4-4 EN 61000-4-5 EN 61000-4-6 EN 61000-3-2 2006 EN 61000-3-3 1995 + A1 2001 + A2 2005 EMC Directive 2004/108/EC EN 55024 1998 + A1 2001 + A2 2003 EN 61000-4-11 2004 EN 61000-4-8 2001 AS/NZS CISPR22 Class B FCC (CFR 47, Part 15) Class B	
Telecom	FCC part 68	
Management	IMC - Intelligent Management Center command-line interface Web browser SNMP Manager Telnet RMON1 FTP IEEE 802.3 Ethernet MIB	
Services	<p>3-year, parts only, global next-day advance exchange (UY865E)</p> <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UY866E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UY869E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UY872E)</p> <p>3-year, 24x7 SW phone support, software updates (UY875E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UY867E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UY870E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UY873E)</p> <p>4-year, 24x7 SW phone support, software updates (UY876E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UY868E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UY871E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UY874E)</p> <p>5-year, 24x7 SW phone support, software updates (UY877E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UY878E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UY879E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UY880E)</p>	

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP MSR920-W Router (NA) (JG208A)



Technical Specifications

Ports	2 RJ-45 autosensing 10/100 WAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX) [†] Duplex [‡] half or full	
	8 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX) [†] Duplex [‡] half or full	
AP characteristics	Radios	Single (b/g)
	Radio operation modes	Client access
	AP operation modes	Autonomous
	Wi-Fi Alliance Certification*	b/g Wi-Fi Certified
	* HP access points and access devices are Wi-Fi Certified, providing our customers with the assurance that these products have met and passed the rigorous interoperability testing performed by the Wi-Fi Alliance Organization. See the Specifications section of this series for more information.	
Physical characteristics	Dimensions	6.3(d) x 9.06(w) x 1.74(h) in. (16 x 23 x 4.42 cm)
	Weight	3.97 lb. (1.8 kg)
Memory and processor	Processor	RISC @ 333 MHz, 256 MB DDR SDRAM, 256 MB flash
Performance	Throughput	up to 100 Kpps (64-byte packets)
	Routing table size	10000 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C)
	Operating relative humidity	5% to 90%
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 90%
Electrical characteristics	Maximum heat dissipation	29 BTU/hr (30.6 kJ/hr)
	DC Voltage	12 V
	Maximum power rating	15 W
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1 [†] /CAN/CSA 22.2 No. 60950-1 [†] /AS/NZS 60950 [†] /EN 60825-1 Safety of Laser Products-Part 1 [†] /EN 60825-2 Safety of Laser Products-Part 2 [†] /IEC 60950-1 [†] /CAN/CSA-C22.2 No. 60950-1-03 [†] /EN 60950-1/A11 [†] /FDA 21 CFR Subchapter J	
Emissions	ANSI C63.4 [†] /EN 55022 Class B [†] /ICES-003 Class B [†] /ETSI EN 300 386 V1.3.3 [†] /EN 61000-4-2 [†] /EN 61000-4-3 [†] /EN 61000-4-4 [†] /EN 61000-4-5 [†] /EN 61000-4-6 [†] /EN 61000-3-2 [†] /2006 [†] /EN 61000-3-3 [†] /1995 +A1 [†] /2001+A2 [†] /2005 [†] /EMC Directive 2004/108/EC [†] /EN 55024 [†] /1998+ A1 [†] /2001 + A2 [†] /2003 [†] /EN 61000-4-11 [†] /2004 [†] /EN 61000-4-8 [†] /2001 [†] /AS/NZS CISPR22 Class B [†] /FCC (CFR 47, Part 15) Class B	
Telecom	FCC part 68	

Technical Specifications

Management IMC - Intelligent Management Center™command-line interface™Web browser™SNMP Manager™Telnet™RMON1™FTP™IEEE 802.3 Ethernet MIB

Services

- 3-year, parts only, global next-day advance exchange (UY881E)
- 3-year, 4-hour onsite, 13x5 coverage for hardware (UY882E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware (UY885E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UY888E)
- 3-year, 24x7 SW phone support, software updates (UY891E)
- 4-year, 4-hour onsite, 13x5 coverage for hardware (UY883E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware (UY886E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UY889E)
- 4-year, 24x7 SW phone support, software updates (UY892E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UY884E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UY887E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UY890E)
- 5-year, 24x7 SW phone support, software updates (UY893E)
- 3 Yr 6 hr Call-to-Repair Onsite (UY894E)
- 4 Yr 6 hr Call-to-Repair Onsite (UY895E)
- 5 Yr 6 hr Call-to-Repair Onsite (UY896E)

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

<p>Standards and protocols (applies to all products in series)</p>	<p>BGP</p> <ul style="list-style-type: none"> RFC 1163 Border Gateway Protocol (BGP) RFC 1267 Border Gateway Protocol 3 (BGP-3) RFC 1657 Definitions of Managed Objects for BGPv4 RFC 1771 BGPv4 RFC 1772 Application of the BGP RFC 1773 Experience with the BGP-4 Protocol RFC 1774 BGP-4 Protocol Analysis RFC 1965 BGP4 confederations RFC 1997 BGP Communities Attribute RFC 1998 PPP Gandalf FZA Compression Protocol RFC 2385 BGP Session Protection via TCP MD5 RFC 2439 BGP Route Flap Damping <p>Denial of service protection</p> <ul style="list-style-type: none"> CPU DoS Protection Rate Limiting by ACLs <p>Device management</p> <ul style="list-style-type: none"> RFC 1305 NTPv3 RFC 1945 Hypertext Transfer Protocol -- HTTP/1.0 	<ul style="list-style-type: none"> RFC 3036 LDP Specification RFC 3046 DHCP Relay Agent Information Option RFC 3065 Support AS confederation RFC 3137 OSPF Stub Router Advertisement RFC 3209 RSVP-TE Extensions to RSVP for LSP Tunnels RFC 3210 Applicability Statement for Extensions to RSVP for LSP-Tunnels RFC 3212 Constraint-Based LSP setup using LDP (CR-LDP) RFC 3214 LSP Modification Using CR-LDP RFC 3215 LDP State Machine RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS) RFC 3277 IS-IS Transient Blackhole Avoidance RFC 3279 Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile RFC 3392 Support BGP capabilities advertisement
---	--	---

Technical Specifications

RFC 2271 FrameWork
RFC 2452 MIB for TCP6
RFC 2454 MIB for UDP6

General protocols

IEEE 802.1D MAC Bridges
IEEE 802.1p Priority
IEEE 802.1Q VLANs
IEEE 802.1s Multiple Spanning Trees
IEEE 802.1w Rapid Reconfiguration of Spanning Tree
RFC 768 UDP
RFC 783 TFTP Protocol (revision 2)
RFC 791 IP
RFC 792 ICMP
RFC 793 TCP
RFC 826 ARP
RFC 854 TELNET
RFC 855 Telnet Option Specification
RFC 856 TELNET
RFC 858 Telnet Suppress Go Ahead Option
RFC 894 IP over Ethernet
RFC 925 Multi-LAN Address Resolution
RFC 950 Internet Standard Subnetting Procedure
RFC 959 File Transfer Protocol (FTP)
RFC 1006 ISO transport services on top of the TCP-
Version 3
RFC 1027 Proxy ARP
RFC 1034 Domain Concepts and Facilities
RFC 1035 Domain Implementation and
Specification
RFC 1042 IP Datagrams
RFC 1058 RIPv1
RFC 1071 Computing the Internet Checksum
RFC 1091 Telnet Terminal-Type Option
RFC 1122 Host Requirements
RFC 1141 Incremental updating of the Internet
checksum
RFC 1142 OSI IS-IS Intra-domain Routing Protocol
RFC 1144 Compressing TCP/IP headers for
low-speed serial links
RFC 1195 OSI ISIS for IP and Dual Environments
RFC 1256 ICMP Router Discovery Protocol (IRDP)
RFC 1293 Inverse Address Resolution Protocol
RFC 1315 Management Information Base for Frame

RFC 3526 More Modular Exponential (MODP)
Diffie-Hellman groups for Internet Key Exchange
(IKE)
RFC 3564 Requirements for Support of
Differentiated Services-aware MPLS Traffic
Engineering
RFC 3602 The AES-CBC Cipher Algorithm and Its
Use with IPsec
RFC 3706 A Traffic-Based Method of Detecting
Dead Internet Key Exchange (IKE) Peers
RFC 3784 ISIS TE support
RFC 3786 Extending the Number of IS-IS LSP
Fragments Beyond the 256 Limit
RFC 3847 Restart signaling for IS-IS

IP multicast

RFC 1112 IGMP
RFC 2236 IGMPv2
RFC 2283 Multiprotocol Extensions for BGP-4
RFC 2362 PIM Sparse Mode
RFC 2934 Protocol Independent Multicast MIB for
IPv4
RFC 3376 IGMPv3

IPv6

RFC 1981 IPv6 Path MTU Discovery
RFC 2080 RIPng for IPv6
RFC 2292 Advanced Sockets API for IPv6
RFC 2373 IPv6 Addressing Architecture
RFC 2460 IPv6 Specification
RFC 2461 IPv6 Neighbor Discovery
RFC 2462 IPv6 Stateless Address Auto-configuration
RFC 2463 ICMPv6
RFC 2464 Transmission of IPv6 over Ethernet
Networks
RFC 2472 IP Version 6 over PPP
RFC 2473 Generic Packet Tunneling in IPv6
RFC 2529 Transmission of IPv6 Packets over IPv4
RFC 2545 Use of MP-BGP-4 for IPv6
RFC 2553 Basic Socket Interface Extensions for IPv6
RFC 2740 OSPFv3 for IPv6
RFC 3056 Connection of IPv6 Domains via IPv4
Clouds
RFC 3513 IPv6 Addressing Architecture
RFC 3596 DNS Extension for IPv6

Technical Specifications

Relay DTEs

RFC 1332 The PPP Internet Protocol Control Protocol (IPCP)
RFC 1333 PPP Link Quality Monitoring
RFC 1334 PPP Authentication Protocols (PAP)
RFC 1349 Type of Service
RFC 1350 TFTP Protocol (revision 2)
RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP)
RFC 1381 SNMP MIB Extension for X.25 LAPB
RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point Protocol
RFC 1472 The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol
RFC 1490 Multiprotocol Interconnect over Frame Relay
RFC 1519 CIDR
RFC 1534 DHCP/BOOTP Interoperation
RFC 1542 Clarifications and Extensions for the Bootstrap Protocol
RFC 1552 The PPP Internetworking Packet Exchange Control Protocol (IPXCP)
RFC 1577 Classical IP and ARP over ATM
RFC 1613 Cisco Systems X.25 over TCP (XOT)
RFC 1624 Incremental Internet Checksum
RFC 1631 NAT
RFC 1638 PPP Bridging Control Protocol (BCP)
RFC 1661 The Point-to-Point Protocol (PPP)
RFC 1662 PPP in HDLC-like Framing
RFC 1695 Definitions of Managed Objects for ATM Management Version 8.0 using SMIv2
RFC 1701 Generic Routing Encapsulation
RFC 1702 Generic Routing Encapsulation over IPv4 networks
RFC 1721 RIP-2 Analysis
RFC 1722 RIP-2 Applicability
RFC 1723 RIP v2
RFC 1795 Data Link Switching—Switch-to-Switch Protocol AIW DLSw RIG—DLSw Closed Pages, DLSw Standard Version 1
RFC 1812 IPv4 Routing
RFC 1829 The ESP DES—CBC Transform
RFC 1877 PPP Internet Protocol Control Protocol

MIBs

RFC 1213 MIB II
RFC 1229 Interface MIB Extensions
RFC 1286 Bridge MIB
RFC 1493 Bridge MIB
RFC 1573 SNMP MIB II
RFC 1724 RIPv2 MIB
RFC 1757 Remote Network Monitoring MIB
RFC 1850 OSPFv2 MIB
RFC 2011 SNMPv2 MIB for IP
RFC 2012 SNMPv2 MIB for TCP
RFC 2013 SNMPv2 MIB for UDP
RFC 2233 Interfaces MIB
RFC 2454 IPV6-UDP-MIB
RFC 2465 IPV6 MIB
RFC 2466 ICMPv6 MIB
RFC 2618 RADIUS Client MIB
RFC 2620 RADIUS Accounting MIB
RFC 2674 802.1p and IEEE 802.1Q Bridge MIB
RFC 2737 Entity MIB (Version 2)
RFC 2863 The Interfaces Group MIB
RFC 2933 IGMP MIB
RFC 3813 MPLS LSR MIB

Network management

IEEE 802.1D (STP)
RFC 1155 Structure of Management Information
RFC 1157 SNMPv1
RFC 1905 SNMPv2 Protocol Operations
RFC 2272 SNMPv3 Management Protocol
RFC 2273 SNMPv3 Applications
RFC 2274 USM for SNMPv3
RFC 2275 VACM for SNMPv3
RFC 2575 SNMPv3 View-based Access Control Model (VACM)
RFC 3164 BSD syslog Protocol

OSPF

RFC 1245 OSPF protocol analysis
RFC 1246 Experience with OSPF
RFC 1587 OSPF NSSA
RFC 1765 OSPF Database Overflow
RFC 1850 OSPFv2 Management Information Base (MIB), traps

Technical Specifications

Extensions for Name Server Addresses	RFC 2328 OSPFv2
RFC 1944 Benchmarking Methodology for Network Interconnect Devices	RFC 2370 OSPF Opaque LSA Option
RFC 1973 PPP in Frame Relay	RFC 3101 OSPF NSSA
RFC 1974 PPP Stac LZS Compression Protocol	QoS/CoS
RFC 1990 The PPP Multilink Protocol (MP)	IEEE 802.1P (CoS)
RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)	RFC 2474 DS Field in the IPv4 and IPv6 Headers
RFC 2091 Trigger RIP	RFC 2475 DiffServ Architecture
RFC 2131 DHCP	RFC 2597 DiffServ Assured Forwarding (AF)
RFC 2132 DHCP Options and BOOTP Vendor Extensions	RFC 2598 DiffServ Expedited Forwarding (EF)
RFC 2166 APPN Implementer's Workshop Closed Pages Document DLSw v2.0 Enhancements	RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP
RFC 2205 Resource ReSerVation Protocol (RSVP) - Version 1 Functional Specification	Security
RFC 2280 Routing Policy Specification Language (RPSL)	IEEE 802.1X Port Based Network Access Control
RFC 2284 EAP over LAN	RFC 1321 The MD5 Message-Digest Algorithm
RFC 2338 VRRP	RFC 2082 RIP-2 MD5 Authentication
RFC 2364 PPP Over AAL5	RFC 2104 Keyed-Hashing for Message Authentication
RFC 2374 An Aggregatable Global Unicast Address Format	RFC 2138 RADIUS Authentication
RFC 2451 The ESP CBC-Mode Cipher Algorithms	RFC 2209 RSVP-Message Processing
RFC 2453 RIPv2	RFC 2246 Transport Layer Security (TLS)
RFC 2510 Internet X.509 Public Key Infrastructure Certificate Management Protocols	RFC 2716 PPP EAP TLS Authentication Protocol
RFC 2511 Internet X.509 Certificate Request Message Format	RFC 2865 RADIUS Authentication
RFC 2516 A Method for Transmitting PPP Over Ethernet (PPPoE)	RFC 2866 RADIUS Accounting
RFC 2644 Directed Broadcast Control	RFC 3567 Intermediate System (IS) to IS Cryptographic Authentication
RFC 2661 L2TP	VPN
RFC 2663 NAT Terminology and Considerations	RFC 2403 - HMAC-MD5-96
RFC 2684 Multiprotocol Encapsulation over ATM Adaptation Layer 5	RFC 2404 - HMAC-SHA1-96
RFC 2694 DNS extensions to Network Address Translators (DNS _z ALG)	RFC 2405 - DES-CBC Cipher algorithm
RFC 2702 Requirements for Traffic Engineering Over MPLS	RFC 2547 BGP/MPLS VPNs
RFC 2747 RSVP Cryptographic Authentication	RFC 2796 BGP Route Reflection - An Alternative to Full Mesh IBGP
RFC 2763 Dynamic Name-to-System ID mapping support	RFC 2842 Capabilities Advertisement with BGP-4
RFC 2765 Stateless IP/ICMP Translation Algorithm (SIIT)	RFC 2858 Multiprotocol Extensions for BGP-4
	RFC 2918 Route Refresh Capability for BGP-4
	RFC 3107 Carrying Label Information in BGP-4
	IPsec
	RFC 1828 IP Authentication using Keyed MD5
	RFC 2401 IP Security Architecture
	RFC 2402 IP Authentication Header
	RFC 2406 IP Encapsulating Security Payload

Technical Specifications

RFC 2766 Network Address Translation - Protocol Translation (NAT-PT)	RFC 2407 - Domain of interpretation
RFC 2784 Generic Routing Encapsulation (GRE)	RFC 2410 - The NULL Encryption Algorithm and its use with IPsec
RFC 2787 Definitions of Managed Objects for VRRP	RFC 2411 IP Security Document Roadmap
RFC 2961 RSVP Refresh Overhead Reduction Extensions	RFC 2412 - OAKLEY
RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS	RFC 2865 - Remote Authentication Dial In User Service (RADIUS)
RFC 2973 IS-IS Mesh Groups	IKEv1
RFC 2993 Architectural Implications of NAT	RFC 2865 - Remote Authentication Dial In User Service (RADIUS)
RFC 3022 Traditional IP Network Address Translator (Traditional NAT)	RFC 3748 - Extensible Authentication Protocol (EAP)
RFC 3027 Protocol Complications with the IP Network Address Translator	
RFC 3031 Multiprotocol Label Switching Architecture	

To learn more, visit www.hp.com/networking

© Copyright 2010-2012 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.